

On Approximation Intractability of the Bandwidth Problem

Gunter Blache* Marek Karpinski† Jürgen Wirtgen‡

Abstract

The *bandwidth problem* is the problem of enumerating the vertices of a given graph G such that the maximum difference between the numbers of adjacent vertices is *minimal*. The problem has a long history and a number of applications. There was not much known about approximation hardness of this problem till recently. Karpinski and Wirtgen [KW 97] proved recently that there are no polynomial time approximation algorithms with an absolute error guarantee of $n^{1-\epsilon}$ for any $\epsilon > 0$ unless $P = NP$.

In this paper we show, that there is no *PTAS* for the bandwidth problem unless $P = NP$, even for the trees. More precisely we prove that there are no polynomial time approximation algorithms for general graphs with an *approximation ratio* better than **1.5**, and for the trees with an *approximation ratio* better than $4/3 \approx \mathbf{1.333}$.

*Dept. of Computer Science, University of Bonn, 53117 Bonn. Email: blache@cs.bonn.edu.

†Dept. of Computer Science, University of Bonn, 53117 Bonn, and International Computer Science Institute, Berkeley, California. Research partially supported by DFG Grant KA 673/4-1, by the ESPRIT BR Grants 7097 and EC-US 030, and by the Max-Planck Research Prize. Email: marek@cs.bonn.edu.

‡Dept. of Computer Science, University of Bonn, 53117 Bonn. Research partially supported by the ESPRIT BR Grants 7097 and EC-US 030. Email: wirtgen@cs.bonn.edu

1 Introduction

The bandwidth problem on graphs has a very long and interesting history and a number of practical applications cf. [CCDG 82].

Formally the bandwidth minimization problem is defined as follows. Let $G = (V, E)$ be a simple graph on n vertices. A numbering (or layout) of G is a one-to-one mapping $f : V \rightarrow \{1, \dots, n\}$. The bandwidth $B(f, G)$ of this numbering is defined by

$$B(f, G) = \max\{|f(v) - f(w)| : \{v, w\} \in E\},$$

the greatest distance between adjacent vertices in G corresponding to f . The bandwidth $B(G)$ is then

$$B(G) = \min_{f \text{ is a numbering of } G} \{B(f, G)\}$$

Clearly the bandwidth of G is the greatest bandwidth of its components. Therefore, we assume without loss of generality that the input graph is connected.

The problem of constructing the bandwidth of a graph is NP -hard (Papadimitriou [Pa 76]), even for trees with maximum degree 3 [GGJK 78]. There are only few cases for which the optimal layout can be constructed in polynomial time [GGJK 78], [Sa 80], [Ch 88], [Sm 95].

To date there was not much known about approximation hardness of the bandwidth. Recently Feige [Fe 97] constructed an approximation algorithm constructing a layout within a polylogarithmic factor of the optimum. This algorithm is based on volume respecting embeddings which are extensions of small distortion embeddings of Linial, London and Rabinovich [LLR 95].

For some special classes of graphs like caterpillars (cf. [HMM 91]) there were polynomial time $\log(n)$ -approximation algorithms known. A caterpillar is a special kind of a tree consisting of a simple chain, the body, with an arbitrary number of simple chains, the hairs, attached to the body by coalescing an endpoint of the added chain with a vertex of the body. For this special class of trees the bandwidth problem was also shown to be NP -hard [Mö 86]. Karpinski, Wirtgen and Zelikovsky [KWZ 97] constructed a 3-approximation algorithm for δ -dense graphs. A graph G is δ -dense, if the minimum degree $\delta(G)$ is at least δn . We call it everywhere dense, if it is δ -dense for some $\delta > 0$.

The design of approximation algorithms for NP -hard optimization problems became an important field of research in recent years. In the best of situations we are able to find approximation algorithms which work in polynomial time and approximate optimal solutions within an arbitrary given constant. Such meta-algorithms are called polynomial time approximation schemes ($PTAS$ s), cf., eg., [Ho 97]. For the dense instances of MAX - SNP problems [PY 91], the existence of $PTAS$ has been proven by Arora, Karger and Karpinski [AKK 95]. Most of these algorithms had one thing in common, namely their running times are bounded by $n^{O(f(1/\epsilon))}$ where the approximation ratio is $r = 1 + \epsilon$. The algorithms are becoming more practical if their running times are functions of the form $g(1/\epsilon)n^{O(1)}$. These algorithms are called efficient polynomial approximation schemes ($EPTAS$ s). There has been recently some progress in this direction. Fernandez de la Vega [Fe 96] designed a randomized algorithm for the MAX - CUT problem, which runs in $2^{(1/\epsilon)^{O(1)}}n^{O(1)}$

time (removing dependence on ϵ in the exponent of n). Frieze and Kannan [FK 96] obtained similar bounds for dense instances of some *MAX-SNP*-hard problems using an algorithmic version of Szemerédi's regularity lemma. Another improvement was given in Goldreich, Goldwasser and Ron [GGR 96], and in Frieze and Kannan [FK 97].

In [KW 97] Karpinski and Wirtgen relate the parameterized complexity theory [DF 92] to the notion of *EPTASs* to show, that there are no *EPTASs* for the bandwidth problem, under certain natural conditions.

Another open problem was whether there exist absolute approximation algorithms for the bandwidth problem. We say, a solution S is a absolute r -approximation to the optimum OPT , if $S \leq OPT + r$ (in the case of minimization problems). In [KW 97] it was shown, that there are no absolute $n^{1-\epsilon}$ -approximation algorithms for the bandwidth problem (even if restricted to dense graphs), unless $P = NP$.

This paper is organized as follows. In Section 2 we prove, that it is *NP*-hard to construct a *PTAS* for trees. Section 2.1 shows that we get better hardness bounds for general graphs.

2 *NP*-Hardness of the Bandwidth Approximation

We are going to show a *gadgetreduction* from the *3SAT* problem to the bandwidth problem restricted to trees. For simplicity, we can assume that each clause contains exactly 3 literals (cf. [Pa 76]). Let be $\phi(x) = \bigwedge_{i=1}^m c_i$ an instance of *3SAT* on n variables. We will construct in polynomial time a tree $T = T_\phi$, such that $\phi \in 3SAT$ iff $B(T) \leq b$, b will be specified later. We use parameters $p, s, \gamma, \gamma_{1..3}^{S,U,V}$ which will be chosen suitable in $n^{O(1)}$. For simplicity reasons, we will define $d = 3 + n + 2m$. Later we will deduce all parameters from s and γ . For the proof of *NP*-hardness of the decision problem, they can be chosen freely from $n^{O(1)}$, as long as they satisfy

$$\gamma + s \geq 3n + 6m \tag{1}$$

For the proof of the approximation hardness we will set them explicitly.

The construction of T starts with a center vertex c . There are two subgraphs S and U , one subgraph L_y for each literal y , and for each clause c_j , four subgraphs C_j^1, \dots, C_j^4 , which are all attached to c . At the outer ends of S and U we attach two subgraphs V_S and V_U (see Figure 1).

The subgraphs L_{x_i} and $L_{\bar{x}_i}$ consist of a line of $m + n$ components. Every component has a line of $2d$ nodes and a star of size s attached to the node with the number $d + 3 + i$. The $d + 1$ -th node of the $m + i$ -th component has a star of size s . Moreover, the $d + 1$ -th node of every j -th component has a star of size s attached through an intermediate node iff x_i (or \bar{x}_i) satisfies the clause c_j (Figure 2).

The four lines for every clause consist of $m + n$ components as well. Every component has a star attached to every node with number $d + 3 + n + j$. The lines C_j^1 and C_j^2 receive one star at the $d + 1$ -th node of the j -th component (Figure 3). The remaining lines C_j^3 and C_j^4 (Figure 4) are kept for consistency.




Figure 1: Overview of the structure of T

The component of the subgraphs S , U and V is a graph with a backbone of length $2d$. The first d nodes have stars of size p (called *barriers*), the following 3 nodes have a star of size γ_1, γ_2 and γ_3 respectively (called *pockets*). The remaining n nodes have a star of size γ , the last $2m$ nodes a star of size $\gamma - 1$ attached (referred to as *buckets*). When built into the subgraphs, the γ_i are replaced by $\gamma_i^{S,U,V}$ respectively.

The subgraphs S and U are constructed from m components and are joined directly with the center node c (Figure 5). The subgraph V is made of n components plus an additional barrier at the end (Figure 6). Two copies are built into the graph: one at the end of S (subsequently called V_S) and U (called V_U).

We set b to be

$$b = n + 2m + \gamma + s + 1 \quad (2)$$

The barriers should have space for exactly $n + 2m$ nodes, so that $n + 2m$ lines may be layed through them. The three pockets of S , the first two of U and the first of V_S and V_U will need extra space for s nodes. It is easy to see, that we can choose our parameters such that in each of this parts the bandwidth will be b :

$$p = \gamma + s$$

$$\begin{array}{lll} \gamma_1^S = \gamma - 2 & \gamma_2^S = \gamma - 1 & \gamma_3^S = \gamma \\ \gamma_1^U = \gamma - 2 & \gamma_2^U = \gamma & \gamma_3^U = \gamma + s \\ \gamma_1^V = \gamma - 1 & \gamma_2^V = \gamma + s & \gamma_3^V = \gamma + s \end{array}$$

This construction is polynomially bounded in n . There are one central node, $4d(n+m) + 2d$ nodes of the backbone, $2(n+m)$ barriers of dp nodes, $m(\gamma_1^S + \gamma_2^S + \gamma_3^S)$ nodes in the pockets of S , $m(\gamma_1^U + \gamma_2^U + \gamma_3^U)$ in those of U and $n(\gamma_1^V + \gamma_2^V + \gamma_3^V)$ in each of V_S and V_U . $2(m+n)n$ stars of size γ and $2(m+n)2m$ stars of size $\gamma - 1$ are in the buckets of S, U, V_S and V_U and $d(b-1)$ in the ending barriers. The $2n$ lines for the literals each have $2d(m+n)$ nodes in the line, a star of size s connected through an intermediate node and $(m+n)s$ in the stars for the buckets. Together they contain $3m$ stars of size s (since it is $3SAT$) plus the additional intermediate node. $4m$ lines for the clauses each consist of $2d(m+n)$ nodes and $m+n$ stars of size s plus the additional node, $2m$ of them have an additional star of size s attached to an intermediate node. It turns out that the tree has $1 + (4d(m+n) + 2d)b$ nodes. Since the diameter is $4d(m+n) + 2d$, b is a strict lower bound for the bandwidth of T .




Figure 2: Line of x_i , occurring in clause 1 and h

Lemma 2.1 For every 3SAT-formula ϕ , T_ϕ has a minimum layout f with

$$B(f, T_\phi) \leq b$$

iff ϕ is satisfiable, and a minimum layout g with $B(g, T_\phi) \geq b \cdot \min\{\frac{3}{2}, 1 + \lceil \frac{s}{3b} \rceil\}$ iff ϕ is not satisfiable.

Proof: Let ϕ be satisfiable. Then there is an assignment a , such that at most two literals of every clause are not satisfied. The layout is given as follows: S , V_S and the lines of the satisfied literals are folded to the left and U , V_U and the lines of the unsatisfied literals are folded to the right of c . C_1^j and C_2^j are folded to the left, if two literals in c_j are not satisfied, one to the left and one to the right, if one literal is not satisfied and both to the right, if all are satisfied. The other two are folded in the opposite side. This layout has bandwidth b , because every pocket in S has exactly 3 stars of size s , every pocket in U has exactly 2 stars of size s and every pocket in both V_S and V_U has exactly one star of size s . Because $n + 2m$ lines are folded to the same side, the buckets have $n + 2m$ stars of size s . The values of $\gamma, \gamma_{1.3}^{S,U,V}$ were chosen, so that all these stars have enough space.

Now suppose ϕ is not satisfiable. Then there are four possibilities for a layout:

1. Both S and U (and with them V_S and V_U) are folded to the same side. Then $2p + 2$ is a lower bound for the bandwidth. To distinguish this case from the satisfied one, we required (1). Thus

$$s + \gamma \geq 3n + 6m$$




Figure 3: Line C_j^1 and C_j^2

$$\begin{aligned}
 4s + 4\gamma + 4 &> 3(n + 2m + \gamma + s + 1) \\
 4p + 4 &> 3b \\
 2p + 2 &> \frac{3}{2}b
 \end{aligned}$$

2. The assignment on which the layout is based, is not valid, i.e. $\exists i : x_i = \bar{x}_i$. Then, two stars of size s will need to be squeezed into the i -th pocket (either in V_S or V_U). The best way to do this is to spread the nodes of the star in the three neighboring sections. So we have

$$B(T) \geq b + \left\lceil \frac{s}{3} \right\rceil \quad (3)$$

3. The layout is based on a valid assignment s , but at least one clause is not satisfied : $\exists j : c_j(a) = 0$. The pockets of the unsatisfied clause have therefore three stars of size s . But because there is only space for two stars, the third one is spread over the three neighboring sections. So we have

$$B(T) \geq b + \left\lceil \frac{s}{3} \right\rceil \quad (4)$$




Figure 4: Line C_j^3 and C_j^4




Figure 5: structure of S and U

4. S and U are folded to different sides (assume S to the left and U to the right) and no pocket has more stars than it should, but the lines are stretched or squeezed to achieve this. E.g. c_j is not satisfied, but the line of one literal is stretched to place the superfluous star into the pocket for c_{j+1} , where only one unsatisfied literal is placed. The line C_1^{j+1} for the clause is folded to the other side and squeezed, so that the star can be placed into the pocket for clause c_j in S .

There are two possibilities to stretch a line: either it is stretched less than d positions, then the star for the bucket will be placed in the barrier and increase the bandwidth by one third of its size:

$$B(T) \geq b + \left\lceil \frac{s}{3} \right\rceil \quad (5)$$

the second possibility is that the line is stretched so much that the star i is placed in the next pocket/bucket $i + 1$. The previous star $i - 1$ is still in the bucket $i - 1$, and so the line with $2d$ nodes has to be stretched over $3d$ positions, and therefore

$$B(T) \geq \frac{3}{2}b \quad (6)$$




Figure 6: structure of V_S and V_U

If a line is squeezed, one star for a bucket is placed in an already occupied area and so the bandwidth increases by a third of its size.

Thus in any case, the bandwidth of the layout of a tree made from an unsatisfied formula is either $\frac{3}{2}b$ or $b + \lceil \frac{s}{3} \rceil$. We show now how to exploit this to prove the approximation hardness of the bandwidth problem on trees.

To show the approximation hardness, we have to assign s and γ to suitable values such that the gap between the bandwidth for satisfied and unsatisfied formulas is a constant multiple of the bandwidth.

$$\begin{aligned} \phi \in 3SAT &\Rightarrow B(T) \leq b \\ \phi \notin 3SAT &\Rightarrow B(T) \geq cb \end{aligned}$$

For the unsatisfied case, we have

$$B(T) \geq \min\left\{2p + 2, \frac{3}{2}b, b + \left\lceil \frac{s}{3} \right\rceil\right\} \quad (7)$$

Choose $\gamma = 3(n + 2m + 1)$, $s = 3l(n + 2m + 1)$, $l \geq 1$.

$$\begin{aligned} B(T) &\geq \min\left\{6(l + 1)(n + 2m + 1) + 2, \right. \\ &\quad \left. \frac{3}{2}(n + 2m + 3(l + 1)(n + 2m + 1) + 1), \right. \\ &\quad \left. n + 2m + 3(l + 1)(n + 2m + 1) + 1 + l(n + 2m + 1)\right\} \\ &\geq \min\left\{6(l + 1)(n + 2m + 1) + 2, \frac{3}{2}(3l + 2)(n + 2m + 1), \right. \\ &\quad \left. 4(l + 1)(n + 2m + 1)\right\} \\ &\geq 4(l + 1)(n + 2m + 1) \end{aligned} \quad (8)$$

So we have for our constant c :

$$\begin{aligned}
c \cdot b &= 4(l+1)(n+2m+1) \\
c \cdot (n+2m+\gamma+s+1) &= 4(l+1)(n+2m+1) \\
c \cdot (n+2m+3(l+1)(n+2m+1)+1) &= 4(l+1)(n+2m+1) \\
c \cdot (3l+4)(n+2m+1) &= 4(l+1)(n+2m+1) \\
c &= \frac{4l+4}{3l+4} \\
c &> \frac{4}{3} - \epsilon
\end{aligned} \tag{9}$$

Thereby we have shown that approximating the bandwidth problem on trees is NP -hard for a factor of $\frac{4}{3} - \epsilon$.

Theorem 2.2 *There is no PTAS for the bandwidth problem on trees, unless $P = NP$. In particular for any $\epsilon > 0$, there is no polynomial time approximation algorithm with an approximation ratio $4/3 - \epsilon \approx 1.333 - \epsilon$, unless $P = NP$.*

2.1 Better Lower Bounds for the General Problem

The critical point in the above construction determining the gap of the bandwidth, is the estimation of a space needed for a star in an already occupied pocket. We can increase this space by replacing the stars on the lines by cliques connected to the lines by new edges and thereby loosing the tree property. The nodes of a clique can themselves be at most b positions apart and are spread over only two sections:

$$B(G) \geq b + \left\lceil \frac{s}{2} \right\rceil$$

Be $\gamma = 2(n+2m+1)$, $s = 2l(n+2m+1)$, $l \geq 2$. Similar transformations lead to the following result for unsatisfied formulas:

$$B(G) \geq 3(l+1)(n+2m+1) \tag{10}$$

And thus we have

$$c > \frac{3}{2} - \epsilon \tag{11}$$

We can now conclude the NP -hardness result for approximating the bandwidth on general graphs with an approximation ratio of $\frac{3}{2} - \epsilon$.

Theorem 2.3 *For any $\epsilon > 0$, there is no polynomial time approximation algorithm with a approximation ratio $1.5 - \epsilon$, unless $P = NP$.*

This construction can be generalized to work for any SAT -formula, even with different numbers of literals in different clauses and multiple occurrences of the same literal in one clause.

3 Open problems

An important question remains open to improve both upper and lower approximation bounds of the general bandwidth problem, closing a huge gap between 1.5 and $O(\log^{11/2} n)$ (cf. [Fe 97]) approximation ratios.

Another interesting computational problem is about the existence of a *PTAS* for the bandwidth problem on dense graphs (cf. [KWZ 97]).

Acknowledgment

We thank Martin Dyer, Alan Frieze, Haim Kaplan, and Uri Zwick for a number of interesting discussions on the subject of this paper.

References

- [AKK 95] Arora, S., Karger, D., Karpinski, M., *Polynomial Time Approximation Schemes for Dense Instances of NP-Hard Problems*, Proc. 27th ACM STOC (1995), pp. 284–293.
- [CCDG 82] Chinn, P., Chvatalova, J., Dewdney, A., Gibbs, N., *The Bandwidth Problem for Graphs and Matrices - A Survey*, Journal of Graph Theory (1982), pp. 223–254.
- [Ch 88] Chung, F., *Labelings of Graphs*, Beineke, L., Wilson, R., ed, Selected Topics in Graph Theory, pp. 151–168, Academic Press, 1988.
- [DF 92] Downey, R., Fellows, M., *Fixed Parameter Intractability*, Proc. 7th IEEE Conf. Structure in Complexity Theory (1992), pp. 36–49.
- [Fe 97] Feige, U., *Approximating the Bandwidth via Volume Respecting Embeddings*, manuscript, 1997.
- [Fe 96] Fernandez-de-la-Vega, W., *MAX-CUT has a Randomized Approximation Scheme in Dense Graphs*, Random Structures and Algorithms **8** (1996), pp. 187–199.
- [FK 96] Frieze, A., Kannan, R., *The Regularity Lemma and Approximation Schemes for Dense Problems*, Proc. 37th IEEE FOCS (1996), pp. 12–20.
- [FK 97] Frieze, A., Kannan, R., *Quick Approximation to Matrices and Applications*, Manuscript, 1997.
- [GGJK 78] Garey, M., Graham, R., Johnson, D., Knuth, D., *Complexity Results For Bandwidth Minimization*, SIAM J. Appl. Math. **34** (1978), pp. 477–495.
- [GGR 96] Goldreich, O., Goldwasser, S., Ron, D., *Property Testing and its Connection to Learning and Approximation*, Proc. 37th IEEE FOCS (1996), pp. 339–348.
- [HMM 91] Haralamides, J., Makedon, F., Monien, B., *Bandwidth Minimization: an Approximation Algorithm for Caterpillars*, Math. Systems Theory **24** (1991), pp. 169–177.

- [Ho 97] Hochbaum, D., ed, *Approximation Algorithms for NP-hard Problems*, PWS Publ. Co., 1997.
- [KW 97] Karpinski, M., Wirtgen, J., *On Approximation Hardness of the Bandwidth Problem*, Technical Report ECCC TR 97-041, 1997.
- [KWZ 97] Karpinski, M., Wirtgen, J., Zelikovsky, A., *An Approximation Algorithm for the Bandwidth Problem on Dense Graphs*, Technical Report ECCC TR 97-017, 1997.
- [LLR 95] Linial, N., London, E., Rabinovich, Y., *The Geometry of Graphs and some of its Algorithmic Applications*, *Combinatorica* **15**(2) (1995), pp. 215–245.
- [Mo 86] Monien, B., *The Bandwidth Minimization Problem for Caterpillars with Hairlength 3 is NP-complete*, *SIAM Journal on Algebraic Discrete Methods* **7** (1986), pp. 505–512.
- [Pa 76] Papadimitriou, C., *The NP-Completeness of the Bandwidth Minimization Problem*, *Computing* **16** (1976), pp. 263–270.
- [PY 91] Papadimitriou, C., Yannakakis, M., *Optimization, Approximation, and Complexity Classes*, *Journal of Computing Systems Science* **43** (1991), pp. 425–440.
- [Sa 80] Saxe, J., *Dynamic Programming Algorithms for Recognizing Small-Bandwidth Graphs*, *SIAM Journal on Algebraic Methods* **1** (1980), pp. 363–369.
- [Sm 95] Smithline, L., *Bandwidth of the Complete k -ary Tree*, *Discrete Mathematics* **142** (1995), pp. 203–212.