



## On the One-Way Function Candidate Proposed by Goldreich

James Cook, UC Berkeley

Omid Etesami, Institute for Research in Fundamental Sciences (IPM)

Rachel Miller, MIT

Luca Trevisan, UC Berkeley

Goldreich [2000] proposed a candidate one-way function based on a bipartite graph of small right-degree  $d$ , where the vertices on the left (resp. right) represent input (resp. output) bits of the function. Each output bit is computed by evaluating a fixed  $d$ -ary binary predicate on the input bits adjacent to that output bit. We study this function when the predicate is either random or linearly depends on many of its input bits. We assume that the graph is a random balanced bipartite graph with right-degree  $d$ .

Inverting this function as a one-way function by definition means finding an element in the preimage of output of this function for a random input. We bound the expected size of this preimage.

Next, using the above bound, we prove that two restricted types of backtracking algorithms called “myopic” and “drunk” backtracking algorithms with high probability take exponential time to invert the function, even if we allow the algorithms use “DPLL” elimination rules. (For drunk algorithms, a similar result was proved by Itsykson [2010].)

We also ran a SAT solver on the satisfiability problem equivalent to the problem of inverting the function, and experimentally observed an exponential increase in running time as a function of the input length.

Categories and Subject Descriptors: F.2.2 [Analysis of Algorithms and Problem Complexity]: Nonnumerical Algorithms and Problems—Complexity of proof procedures; E.3 [Data Encryption]: Code Breaking; I.2.8 [Artificial Intelligence]: Problem Solving, Control Methods, and Search—Backtracking; G.2.1 [Discrete Mathematics]: Combinatorics—Counting Problems

General Terms: Algorithms, Theory, Security

Additional Key Words and Phrases: One-way function, random bipartite graph, average preimage size, restricted backtracking algorithm, proof complexity, DPLL elimination rules

### ACM Reference Format:

James Cook, Omid Etesami, Rachel Miller, and Omid Etesami, 2013. On the One-Way Function Candidate Proposed by Goldreich. *ACM Trans. Comput. Theory* V, N, Article A (January YYYY), 34 pages.  
DOI: <http://dx.doi.org/10.1145/0000000.0000000>

---

This material is based upon work supported by the National Science Foundation under Grant Nos. CCF 1017403 and CCF 0729137, the Natural Sciences and Engineering Research Council of Canada under a PGS award, European Research Council Grant No. 228021-ECCSciEng, IPM (Institute for Research in Fundamental Sciences, Tehran), an NSF SUPERB fellowship, an NDSEG fellowship, and the BSF under grant 2002246.

Authors' addresses: J. Cook, Computer Science Division, UC Berkeley; O. Etesami, (Current address) School of Mathematics, Institute for Research in Fundamental Sciences (IPM), P.O. Box 19395-5746, Tehran, Iran; R. Miller, (Current address) Asana Company; L. Trevisan, (Current address) Computer Science Department, Stanford University.

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies show this notice on the first page or initial screen of a display along with the full citation. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, to republish, to post on servers, to redistribute to lists, or to use any component of this work in other works requires prior specific permission and/or a fee. Permissions may be requested from Publications Dept., ACM, Inc., 2 Penn Plaza, Suite 701, New York, NY 10121-0701 USA, fax +1 (212) 869-0481, or [permissions@acm.org](mailto:permissions@acm.org).

© YYYY ACM 1942-3454/YYYY/01-ARTA \$15.00

DOI: <http://dx.doi.org/10.1145/0000000.0000000>

## 1. INTRODUCTION

Goldreich [2000] proposed a candidate one-way function based on expanders. His construction is parametrized by the choice of a bipartite graph  $G$  with  $n$  vertices per side having right-degree  $d$  (where  $d$  is either constant or grows moderately as  $O(\log n)$ ) and a boolean predicate  $P : \{0, 1\}^d \rightarrow \{0, 1\}$ . To compute the function on input  $x \in \{0, 1\}^n$  we label the vertices on the left by the bits of  $x$ , and then label each vertex on the right by the value of  $P$  applied to the labels of its neighbors. The  $n$  labels on the right constitute the output of the function. Goldreich conjectured that his function is hard to invert when the predicate  $P$  is random and the graph  $G$  is an expander.

Though Goldreich’s function is simple, it may yet be one-way: Even when  $d = O(1)$ , it lies in the complexity class  $NC^0$  of functions whose every output bit depends on a constant number of input bits, and by standard cryptographic assumptions there exist one-way functions and pseudo-random generators computable in  $NC^0$  [Applebaum et al. 2006a; 2006b].

We present a rigorous study of Goldreich’s function when the predicate  $P$  is either random or depends linearly on many of its inputs. We assume that the graph  $G$  is drawn uniformly at random; here we diverge from Goldreich’s original proposal.

### 1.1. Results

Inverting a one-way function  $f$  means finding any  $x' \in f^{-1}(f(x))$ , given  $f(x)$  for a random  $x$ . We begin our analysis of Goldreich’s function by proving an upper bound on the expected size of  $f^{-1}(f(x))$ .

Next we look at backtracking algorithms for inverting Goldreich’s function. A backtracking algorithm exhaustively searches over possible inputs to the function, by assigning, at each step, a value of 0/1 to one of the unassigned input bits, and backtracking whenever an output bit is determined to be incorrect.

We show that for two restricted forms of backtracking algorithms, called “myopic” and “drunk” backtracking algorithms, with extremely high probability the algorithm takes an exponential number of steps to invert. (In the case of non-DPLL drunk algorithms, our results reproduce those of Itsykson [2010] and Miller [2009].) A myopic backtracking algorithm is one in which at each step the algorithm should assign a value for one of the input bits based on only partial knowledge of the output of the function. A drunk backtracking algorithm is one in which the value assigned to the input bits is at each step 0 or 1 uniformly at random.

We further show that these running time lower bounds still hold if we add “DPLL” elimination rules, which allow the algorithms to search the input space more quickly.

Finally, we can express finding an input in the preimage of an output of Goldreich’s function as a satisfiability problem. We solved this satisfiability problem using MiniSAT, a competitive publicly available SAT solver, and observed an exponential increase in running time as a function of the input length.

### 1.2. Techniques and Proof Overview

*1.2.1. The Expected Size of Pre-Images.* To calculate the expected size of the preimage, we first reduce this to computing, for every pair of inputs  $(x, y)$ , the probability PE that a single output bit agrees:  $f(x)_1 = f(y)_1$ . Here, the randomness comes from the uniformly random choice of graph  $G$  used for Goldreich’s function. PE is in turn equal to the probability that the predicate  $P$  outputs the same bit when it receives two  $d$ -bit inputs  $(u, v)$  which are random but bitwise correlated. More precisely, the  $i$ -th pair of bits  $(u_i, v_i)$  is drawn from a probability distribution  $\alpha$  on  $\{0, 1\}^2$  determined by  $(x, y)$ .

We wish to show that a random predicate  $P$  performs well for all possible probability distributions  $\alpha$  over  $\{0, 1\}^2$ . Since we cannot directly apply a union bound over this

infinite set, we instead describe a different, finite set of properties over which we can (Definition 3.7). We show that these finitely many properties together imply that the predicate performs well for every  $\alpha$ . We had to devise this technique in order to extend our result to random predicates, where we had previously only considered predicates that depend linearly on many inputs.

*1.2.2. Lower Bound for Backtracking Algorithms.* Our proof is similar to the proof of Alekhovich et al. [2005] that myopic backtracking algorithms take an exponentially long time to solve systems of linear equations.<sup>1</sup>

Let  $\mathcal{A}$  be a myopic or drunk backtracking algorithm. We pick a random  $x \in \{0, 1\}^n$ , and run  $\mathcal{A}$  on input  $b = f(x)$ . Our goal is to show that  $\mathcal{A}$  will run for a long time before returning any  $x' \in f^{-1}(b)$ , but we begin with an easier goal: to show that  $\mathcal{A}$  will either run for a long time or return a value that is not *exactly* equal to  $x$ . In the case that  $f$  is an injective function, like in the result of Alekhovich et al, these goals are one and the same. But in our general case, we introduce Lemma 3.1 to allow us to reduce the harder goal to the easier goal using our upper bound on the size of preimages.

Our general strategy to prove the easier goal is similar to that of Alekhovich et al: to show first that with high probability  $\mathcal{A}$  will choose an incorrect value for a variable, and second, that it will take a long time to recover from its mistake (using proof complexity lower bounds). We are only able to prove the second part when the mistake the algorithm made is “locally consistent” (Definition 4.4).

At every point during the execution of  $\mathcal{A}$ , its partial truth assignment  $\rho$  can be in one of three states:

1.  $\rho$  is consistent with  $x$ .
2.  $\rho$  is not consistent with  $x$ , but is locally consistent.
3.  $\rho$  is not locally consistent.

We need to show that the algorithm reaches state 2 with high probability.

In order to make our task simpler, we start by modifying  $\mathcal{A}$  so that it becomes a *clever* algorithm that never enters state 3 before it makes a large number of assignments (Lemma 4.13). Then we show (in Lemma 5.1 when  $\mathcal{A}$  is myopic and in Lemma 6.4 when  $\mathcal{A}$  is drunk) that with high probability, the algorithm reaches state 2.

We have to break away in two further ways from the result of Alekhovich et al: First, the predicates we consider are nonlinear. (Linear predicates are not interesting for our study since they allow Goldreich’s function to be inverted using Gaussian elimination.) Therefore, we have to introduce the notion of “ $(h, \epsilon)$ -balanced” predicates and generalize the result for this more general class of predicates. Second, a random graph with non-negligible probability contains small non-expanding sets of nodes. Since unlike Alekhovich et al. we consider random graphs rather than expanders, we have to generalize our results for a weaker notion of expansion which allows such small non-expanding sets.

*1.2.3. DPLL Rules Don’t Help.* DPLL elimination rules prune an algorithm’s backtracking tree to make it faster. These are traditionally defined for algorithms that solve the CNF satisfiability problem. *Unit clause* elimination applies when a clause consists of a single literal  $\ell$ , and *pure literal* elimination applies when the negation  $\bar{\ell}$  does not appear in any clause. In both cases, the algorithm is allowed to prune subtrees in which  $\ell$  is true.

<sup>1</sup>We define myopic algorithms as reading the bits of  $f(x)$  in a restricted way. Here we differ from the definition of Alekhovich et al, who allow a myopic algorithm to see for free the entire CNF formula describing the search problem of inverting  $f$ , with only the signs of literals restricted. It is worth noting that their work considers only linear predicates, a case where the two definitions are equivalent.

We adapt these rules to backtracking algorithms for inverting Goldreich’s function. We show that our lower bound for myopic and drunk backtracking algorithm still applies, because myopic and drunk algorithms without access to the DPLL pruning rules can simulate these rules to achieve similar runtimes. We are considering DPLL rules in a context more general than Alekhnovich et al. [2005], and a “black-box” simulation is new to this work. To simulate the pruning, we make unit clause assignments immediately, but postpone pure literal assignments until the last possible moment. In the case of myopic algorithms, a subtle point arises: it is not clear that a myopic algorithm will be able to gather enough information to find all unit clauses and pure literals. We show that for the parameters of Goldreich’s function that we have chosen — a random graph and a predicate that is random or depends linearly on many inputs — all unit clauses and pure literals can be found without reading too many more bits of the output of the function, so the algorithm remains myopic.

### Related Work

Goldreich [2000] considered the following algorithm (as an obvious first attack) for computing  $x$  given  $y = f(x)$ . The algorithm proceeds in  $n$  steps, revealing the output bits one at a time. Let  $R_i$  be the set of inputs connected to the first  $i$  outputs. Then in the  $i$ th step, the algorithm computes the list  $L_i$  of all strings in  $\{0, 1\}^{R_i}$  which are consistent with the first  $i$  bits of  $y$ . The final list  $L_n$  enumerates the set  $f^{-1}(y)$ . Goldreich proves that if the graph satisfies an expansion condition, then the expected size of one of the sets  $L_i$  is exponentially large, and so this inversion algorithm runs in time exponential in the input length. Panjwani [2001] experimentally verified this result.

The above algorithm is a weaker version of a myopic backtracking algorithm where before assigning values to the bits in  $R_i$ , the algorithm has no knowledge of  $y$  except its first  $i$  bits.<sup>2</sup> For this reason, our lower bounds for myopic algorithms are more general.

Besides Itsykson’s independent lower bound on drunk DPLL backtracking algorithms mentioned before, there has been other further work since the publication of the conference version of this work.

Bogdanov and Qiao [2009] present an efficient algorithm for inverting instances of Goldreich’s function where the number of output bits is much larger than the number of input bits, and the predicate is correlated with one or two of its inputs. Notice that Goldreich’s original proposal suggests that the number of input bits be equal to the number of output bits.

Itsykson and Sokolov [2012; 2013] find a lower bound for the running time of myopic and drunk DPLL algorithms for an explicit construction of Goldreich’s function, which is interesting compared to our results for random graphs. However, their function partitions the input variables into two parts:  $o(n)$  variables which affect the output non-linearly, and  $n - o(n)$  variables which affect the output linearly. The fact that the non-linear part is small allows an algorithm to invert the function in  $2^{o(n)}$  time.

Itsykson and Sokolov [2011] find a lower bound for myopic DPLL algorithms with the addition of a myopic *cut heuristic* which allows the algorithm to remove branches from the backtracking tree. This is significant since previous work, as well as this paper, rely on the fact that a DPLL algorithm would encounter a large subtree containing no solutions and would be forced to explore the entire subtree before continuing. The

<sup>2</sup>We introduce myopic backtracking algorithms in Definitions 2.9 and 2.10. The list  $L_i$  mentioned above corresponds to the nodes at level  $|R_i|$  of the backtracking tree of the myopic backtracking algorithm. To simulate the algorithm considered by Goldreich by a myopic backtracking algorithm, the scheduler of the backtracking algorithm does not need to look at the output to decide which variable to assign next, nor to decide which value to try assigning to that variable first.

hard formulas they consider are systems of linear equations, which are equivalent to instances of Goldreich’s function with an XOR predicate.

Using several assumptions including that Goldreich’s function with predicate  $\text{MAJ}(x_1 \oplus \dots \oplus x_{d/3}, x_{d/3+1} \oplus \dots \oplus x_{2d/3}, x_{2d/3+1} \oplus \dots \oplus x_d)$  is a pseudorandom generator, Applebaum et al. [2010] build a public-key cryptosystem. This assumption is stronger than Goldreich’s original conjecture.

Applebaum [2013] constructs pseudorandom generators based on the assumption that Goldreich’s function with a random predicate and graph is one-way. He constructs a linear-stretch pseudorandom generator in  $NC^0$ , a polynomial-stretch pseudorandom generator when the degree of each output bit is  $\omega(1)$ , and a polynomial-stretch generator in  $NC^0$  with inverse polynomial distinguishing advantage.

## Open Questions

Our work adds motivation for further experimental and rigorous analysis of Goldreich’s construction.

The limitation of the present work is the somewhat artificial nature of both myopic algorithms and drunk algorithms. Myopic algorithms fail to capture certain natural “global” heuristics used in SAT solvers. Since the algorithm is required to work only with partial information on the object given as an input, negative results for myopic algorithms are similar in spirit (but very different technically) to results on “space bounded cryptography.” Drunk algorithms are restricted in a way that is more computational than information-theoretic, but the random selection of variable values is clearly contrived. Despite these limitations, we hope our results will serve as an important step toward lower bounds for more general classes of algorithms.

Another interesting goal would be to show that no “variation of Gaussian elimination” can invert Goldreich’s function when non-linear predicates are used. Unfortunately, it is not clear how to even formalize such a statement. For example, here is an algorithm for inverting Goldreich’s function with predicates of the form  $P(x) = x_1 \oplus \dots \oplus x_{d-2} \oplus (x_{d-1} \wedge x_d)$  which uses a combination of backtracking and Gaussian elimination: first, consider a graph  $H$  on  $n$  vertices, where for every constraint of the form  $x_{i_1} \oplus \dots \oplus x_{i_{d-2}} \oplus (x_{i_{d-1}} \wedge x_{i_d}) = b_j$  there is an edge between the  $i_{d-1}$ -th and  $i_d$ -th vertices. Find a vertex cover for the random graph  $H$ , and backtrack to set the values of the variables corresponding to this vertex cover. Once these variables have been set, the values of the remaining variables can be found using Gaussian elimination. This will give an improved running time (though still exponential) because the vertex cover contains a strict subset of the  $n$  variables.

## 2. DEFINITIONS AND STATEMENT OF THEOREMS

### 2.1. The Problem of Inverting Goldreich’s Function

**DEFINITION 2.1.** *The **one-way function candidate**  $f = f_{P,G} : \{0,1\}^n \rightarrow \{0,1\}^m$  proposed by **Goldreich** is parametrized by*

- a  $d$ -ary predicate  $P : \{0,1\}^d \rightarrow \{0,1\}$ , and
- a bipartite graph  $G$  with  $n$  vertices on the left and  $m$  vertices on the right having right-degree  $d$ .

*We represent the bipartite graph as  $G \in [n]^{m \times d}$  where  $[n] = \{1, \dots, n\}$ . In this representation, the set of vertices on the left is  $L = [n]$ , the set of vertices on the right is  $R = [m]$ , and vertex  $i$  on the right is connected with vertices  $G_{i,1}, \dots, G_{i,d}$  on the left. The function  $f = f_{P,G}$  is defined by*

$$f(x)_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}}) \text{ for each } i \in [m].$$

That is, we evaluate  $P$  over the neighbors of each right vertex.

As we represent the graph as  $G \in [n]^{m \times d}$ , we are implicitly imposing an ordering on the set of edges going out of each vertex on the right.

An algorithm  $A$  for inverting the function  $f$  is said to be successful given some  $b \in \{0, 1\}^m$  if it can return some  $A(b) \in \{0, 1\}^n$  such that  $f(A(b)) = b$ .

**DEFINITION 2.2.** Fix a  $d$ -ary predicate  $P$ . We say that Goldreich’s function  $f_{P,G}$  with random graph  $G$  is **secure** against a class of algorithms if the following holds: For almost every graph  $G$ , for every algorithm  $A$  in the class, for almost every input  $x$ , the algorithm  $A$  given  $b = f_{P,G}(x)$  is not successful in time  $\leq 2^{\Theta(n)}$ . “Almost every graph  $G$ ” and “almost every input  $x$ ” mean with probability  $\geq 1 - 2^{-\Theta(n)}$  over a uniformly random choice of  $x \in \{0, 1\}^n$ , or  $G$  among all bipartite graphs with  $m = n$  right nodes of degree  $d$ . The hidden constants in the asymptotic notation  $\Theta(n)$  in this definition may depend on  $d$ .

## 2.2. Expected Size of the Preimage

**DEFINITION 2.3.** Consider a test on  $d$ -ary predicates, where every  $d$ -ary predicate either passes or fails the test. We define properties (A), (B), (B’), (C) on the test as follows:

- (A). A uniformly random predicate passes the test with probability  $1 - o_d(1)$ ;
- (B). Predicates of the form  $P = x_1 \oplus \dots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  when  $d-h = \Omega(d)$  pass the test;
- (B’). For every constant  $0 \leq c < \frac{1}{2}$ , for large enough  $d$ , predicates of the form  $P = x_1 \oplus \dots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  for  $h \leq cd$  pass the test;
- (C). The test can be performed in time  $2^{O(d)}$ .

**DEFINITION 2.4.** For any fixed function  $f : \{0, 1\}^n \rightarrow \{0, 1\}^m$ , we define the **expected size of the preimage** under  $f$  as

$$\mathbf{E}_{x \sim \text{Unif}(\{0,1\}^n)} [|f^{-1}(f(x))|].$$

When this expected size is  $M$ , we can think that the function  $f$  is  $M$ -to-one on average. We expect that for a good one-way function,  $M$  is not too large.

**THEOREM 2.5.** There exists a test satisfying properties (A), (B), (C) such that whenever the predicate  $P$  passes the test, Goldreich’s  $f_{P,G}$  satisfies

$$\mathbf{E}_{G \sim \text{Unif}([n]^{n \times d})} \mathbf{E}_{x \sim \text{Unif}(\{0,1\}^n)} [|f_{P,G}^{-1}(f_{P,G}(x))|] \leq n^{O(1)} 2^{2^{-\Omega(d)} n}.$$

The details of the test emerge in the proof of the theorem, and are also gathered in Appendix A.

## 2.3. Backtracking Algorithms

**DEFINITION 2.6.** At each step of a **backtracking algorithm**  $A$  for inverting Goldreich’s function, i.e. finding  $x$  such that  $f(x) = b$ , a subset of the variables  $x_1, \dots, x_n$  have been assigned binary values and the rest of the variables are free. At the beginning of the backtracking algorithm, all variables are free. The backtracking algorithm  $A$  stops searching a path further if for some  $i$ , all the variables  $x_{G_{i,1}}, \dots, x_{G_{i,d}}$  have values assigned to them and  $P(x_{G_{i,1}}, \dots, x_{G_{i,d}}) \neq b_i$ . Otherwise,  $A$  chooses an assignment  $x_j \leftarrow a$  where  $x_j$  is a free variable and  $a \in \{0, 1\}$  is a value for  $x_j$ . The algorithm first assigns the value  $a$  to variable  $x_j$  and recursively calls the algorithm. If the algorithm  $A$  does not find  $x$  such that  $f(x) = b$  in this recursion, it recurses again this time assigning  $1 - a$  to  $x_j$ . The algorithm stops when there are no free variables and  $f(x) = b$ .

We consider “drunk” and “myopic” backtracking algorithms.

#### 2.4. Drunk Backtracking Algorithm

DEFINITION 2.7. A backtracking algorithm is said to be drunk if in the assignment  $x_j \leftarrow a$  to the current variable,  $a \in \{0, 1\}$  is uniformly random and independent of  $j$ .

THEOREM 2.8. There exists a test on  $d$ -ary predicates satisfying properties (A), (B’), and (C) such that when predicate  $P$  passes the test, Goldreich’s function  $f_{P,G}$  with random graph  $G$  is secure against the class of drunk backtracking algorithms.

#### 2.5. Myopic Backtracking Algorithm

DEFINITION 2.9. A **myopic** backtracking algorithm  $A$  for inverting  $f_{P,G}$  is one which has a limited view of the given  $b \in \{0, 1\}^m$  for which it wants to find an  $x \in f_{P,G}^{-1}(b)$ . At each step, the algorithm knows a subset of the bits of  $b$ . On the other hand, the algorithm has full knowledge of  $P$  and of  $G$ . In the beginning,  $A$  knows nothing about  $b$ . At each step, the algorithm is allowed to

- either query a bit of  $b$ ,
- or choose a pair  $(j, a)$ ; then assign the value  $a$  to  $x_j$  and recurse; if no  $x \in f^{-1}(b)$  is found during this recursion, then assign  $1 - a$  to  $x_j$  and recurse.

When the algorithm recurses, the knowledge of  $b$  is preserved; but the knowledge of  $b$  is not passed from one recursion tree to a sibling recursion tree. In other words, when we return back from a recursion, we leave behind all the knowledge we gained.

DEFINITION 2.10. A myopic backtracking algorithm is called  $(s, t)$ -myopic if it never tries to read more than  $t$  bits of  $b$  before it has assigned binary values to at least  $s$  variables.

THEOREM 2.11. There exists a test on  $d$ -ary predicates satisfying properties (A), (B’), and (C) such that when predicate  $P$  passes the test, there is  $t = \Theta(n)$  such that for any  $s$  such that  $s/n = 2^{-o(d)}$ , Goldreich’s function  $f_{P,G}$  with random graph  $G$  is secure against the class of  $(s, t)$ -myopic backtracking algorithms. The hidden constant in the asymptotic  $\Theta(n)$  notation depends on  $d$ .

#### 2.6. Backtracking Algorithms with DPLL Elimination Rules

DEFINITION 2.12. Assume we are in the middle of a backtracking algorithm trying to find an element  $x$  in the preimage of  $b$  under  $f_{P,G}$ : A subset of the variables  $x_1, \dots, x_n$  have been assigned binary values and the rest of the variables are free. Let  $x_j$  be a free variable and let  $a \in \{0, 1\}$ . We call  $x_j \leftarrow a$  a **DPLL** assignment if, given all the already-assigned variables, one of the following two situations happens:

- $x_j = a$  is implied from the equation  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$  for some  $i$ ; in this case we say that a **unit clause** exists.
- for all  $i = 1, \dots, m$ , switching the value of  $x_j$  from  $1 - a$  to  $a$  can never change the equations  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$  to become false; in this case we say that a **pure literal** exists.

(The terms “unit clause” and “pure literal” come from the context of CNF formulas: We have adapted the terminology in the context of Goldreich’s function.) When  $x_j \leftarrow a$  is a DPLL assignment, conditioned on the already assigned values for the variables  $x_1, \dots, x_n$  that are not free, if there is no  $x$  in the preimage with  $x_j = a$ , neither is there an  $x$  in the preimage with  $x_j = 1 - a$ .

**DEFINITION 2.13.** *A DPLL backtracking algorithm is similar to an ordinary backtracking algorithm except that at each step, for any existing DPLL assignment  $x_j \leftarrow a$ , we have the option of eliminating  $x_j$  from the list of free variables by assigning  $a$  to  $x_j$  and recursing (and when this recursion finishes, we do not try assigning  $1 - a$  to  $x_j$ .)*

DPLL drunk backtracking algorithms are simply drunk backtracking algorithms that are allowed to eliminate as above free variables  $x_j$  in DPLL assignments  $x_j \leftarrow a$ . Defining DPLL myopic backtracking algorithms involves a certain subtlety: Having access to the set of DPLL assignment  $x_j \leftarrow a$  might reveal extra information about  $b$ . However, we allow a DPLL myopic backtracking algorithm to know the set of DPLL assignments. Yet, we allow this knowledge to be only passed further down in recursions; we do not allow such knowledge to be passed from a recursion tree to a sibling recursion tree. Besides knowing the set of DPLL assignments, an  $(s, t)$ -myopic DPLL backtracking algorithm for finding  $x \in f^{-1}(b)$  may not read more than  $t$  bits of  $b$  before making at least  $s$  non-DPLL assignments to  $x$ .

**THEOREM 2.14.** *Theorem 2.8 and Theorem 2.11 respectively hold for DPLL drunk and DPLL myopic backtracking algorithms as well.*

This theorem, as stated in this section, gives super-polynomial lower bounds on the running time of drunk and myopic DPLL backtracking algorithms for inverting Goldreich's function with non-negligible probability, when the predicate passes the tests mentioned in Theorems 2.8 and 2.11, if  $d$  is large enough but still constant compared to  $n$ . However, if one looks at the proof of the theorem, the same result holds when  $d = o(\log n)$  or when  $d \leq c \log n$  for suitably small positive constant  $c$ .

### 3. EXPECTED SIZE OF THE PREIMAGE

Inverting a candidate one-way function  $f : \{0, 1\}^n \rightarrow \{0, 1\}^m$  is the problem of finding, given  $b \in \{0, 1\}^m$ , an element in the preimage  $f^{-1}(b)$ , where  $b = f(x)$  for  $x \in \{0, 1\}^n$  chosen uniformly at random. The problem of finding  $x$  itself given  $b$  is a harder problem, but as the following lemma shows, these two problems are related via the expected size of the preimages under  $f$ .

**LEMMA 3.1.** *Let  $f : \{0, 1\}^n \rightarrow \{0, 1\}^m$  be a function with expected preimage size  $M = \mathbf{E}_{x \in \{0, 1\}^n} |f^{-1}(f(x))|$ . Let  $\mathcal{A}$  be an algorithm that, given  $b \in \{0, 1\}^m$ , returns  $\mathcal{A}(b) \in \{0, 1\}^n$ . Choose  $x$  uniformly at random from  $\{0, 1\}^n$  and let  $b = f(x)$ , so the probability sample space is  $\{x : x \in \{0, 1\}^n\}$ . Consider the events  $E = \{x : \mathcal{A}(b) = x\}$  and  $F = \{x : \mathcal{A}(b) \in f^{-1}(b)\}$ . We have*

$$\Pr[F] \leq 2\sqrt{M \Pr[E]}.$$

**PROOF.** Consider the event  $H = \{x : |f^{-1}(b)| \leq M'\}$ , where we will specify  $M' > 0$  shortly. We have  $\Pr[F] \leq \Pr[F \cap H] + \Pr[H^c]$ , where  $H^c$  is the complement of  $H$ . To upper-bound  $\Pr[H^c]$ , we use Markov's inequality and get  $\Pr[H^c] \leq M/M'$ . We also have

$$\Pr[E] \geq \Pr[E|F \cap H] \cdot \Pr[F \cap H] \geq \frac{1}{M'} \cdot \Pr[F \cap H],$$

so we get  $\Pr[F \cap H] \leq M' \Pr[E]$ . We complete the proof by taking  $M' = \sqrt{M/\Pr[E]}$ , so that

$$\Pr[F] \leq \Pr[F \cap H] + \Pr[H^c] \leq M' \Pr[E] + M/M' = 2\sqrt{M \Pr[E]} \quad \square$$

The rest of this section is devoted to proving the upper bound of Theorem 2.5 on the expected size of the preimage for Goldreich's function. See Section 1.2.1 for an overview. This theorem was shown for  $h = 2$  and  $Q(x, y) = x \wedge y$  in the conference



version of this paper [Cook et al. 2009]. Itsykson [2010] pointed out that the same proof works for general predicates  $Q$  for  $h + 1 < d/4$ . The proof for random predicates is original to this work. We also mention that Panjwani [2001] has previously done some experimental analysis of the size of preimages in Goldreich's function, composed with itself many times.

Theorem 2.5 concerns the expected size of preimages  $|f_{P,G}^{-1}(f_{P,G}(x))|$  of Goldreich's function  $f_{P,G}$ . We assume the predicate  $P$  satisfies a test which we will define later, and choose the graph  $G \in [n]^{n \times d}$  and the input  $x \in \{0, 1\}^n$  uniformly at random.

We begin by observing that the expected size of the preimage  $M$  is equal to  $2^{-n}$  times the number of colliding pairs of inputs:

$$\begin{aligned} M &= \mathbf{E}_{G \sim \text{Unif}([n]^{n \times d})} \mathbf{E}_{x \sim \text{Unif}(\{0,1\}^n)} [|f_{P,G}^{-1}(f_{P,G}(x))|] \\ &= 2^{-n} \mathbf{E}_{G \sim \text{Unif}([n]^{n \times d})} |\{x, y \in \{0, 1\}^n : f_{P,G}(x) = f_{P,G}(y)\}| \end{aligned}$$

This allows us to express the expected preimage size in terms of collision probabilities:

$$M = 2^{-n} \sum_{x, y \in \{0,1\}^n} \Pr_{G \sim \text{Unif}([n]^{n \times d})} [f_{P,G}(x) = f_{P,G}(y)]$$

Recall that the  $i$ -th output bit of Goldreich's function  $f_{P,G}$  depends on the input bits  $x_{G_{i,1}}, \dots, x_{G_{i,d}}$ . Since the input indices  $G_{i,1}, \dots, G_{i,d}$  are chosen independently at random for each  $i$ , for a fixed  $x$  and  $y$ , the events  $f_{P,G}(x)_i = f_{P,G}(y)_i$  for different values of  $i$  are independent:

$$M = 2^{-n} \sum_{x, y \in \{0,1\}^n} \prod_{i=1}^n \Pr_{G \sim \text{Unif}([n]^{n \times d})} [f_{P,G}(x)_i = f_{P,G}(y)_i]$$

We introduce the notation  $\text{PE}_P(x, y) = \Pr_{G \sim \text{Unif}([n]^{n \times d})} [f_{P,G}(x)_i = f_{P,G}(y)_i]$  (for **P**robability of **E**quality) noticing that the value is the same for every index  $i$ :

$$M = \sum_{x, y \in \{0,1\}^n} (2^{-1} \text{PE}_P(x, y))^n \quad (1)$$

Now, suppose there are  $n_{ab}$  indices  $j$  such that  $x_j = a$  and  $y_j = b$ ;  $n_{00} + n_{01} + n_{10} + n_{11} = n$ . Then  $\text{PE}_P(x, y)$  depends only on the predicate  $P$  and the four numbers  $n_{ab}$ , since the equality  $f_{P,G}(x)_i = f_{P,G}(y)_i$  depends only on the pairs of bits  $(x_{G_{i,1}}, y_{G_{i,1}}), \dots, (x_{G_{i,d}}, y_{G_{i,d}})$ . This motivates the following definition.

**DEFINITION 3.2.**

- For a pair  $(x, y) \in (\{0, 1\}^n)^2$ , define **NA** (for *Number of Appearances*) by  $\mathbf{NA}(x, y) = (n_{00}, n_{01}, n_{10}, n_{11})$ , where  $n_{ab}$  is the number of indices  $i$  such that  $x_i = a$  and  $y_i = b$ . If we let  $\Delta^2(n) = \{\beta : \{0, 1\}^2 \rightarrow \mathbf{N} \mid \sum \beta = n\}$  be the set of ways of putting  $n$  balls into four bins, then  $\mathbf{NA}(x, y) \in \Delta^2(n)$ . Furthermore, if we let  $\Delta^2 = \{p : \{0, 1\}^2 \rightarrow \mathbf{R}^{\geq 0} \mid \sum p = 1\}$  be the set of probability distributions over  $\{0, 1\}^2$ , then  $\mathbf{NA}(x, y)/n \in \Delta^2$ . For example,  $\mathbf{NA}(0110, 1000)/4 = (1/4, 1/4, 1/2, 0)$ .
- For  $\alpha \in \Delta^2$ , we define  $\alpha^d$  to be the distribution over  $(\{0, 1\}^d)^2$  such that  $(x, y) \sim \alpha^d$  means each pair  $(x_i, y_i)$  is distributed according to  $\alpha$  independently. For example, if  $\alpha$  is the uniform distribution,  $\alpha^d$  is also the uniform distribution, and if  $\alpha$  assigns a probability of 1 to the string 01, then  $\alpha^d$  assigns a probability of 1 to the pair

$(0 \cdots 0, 1 \cdots 1)$ . Finally,  $\mathcal{H}(\alpha)$  denotes the base-2 entropy of the distribution:  $\mathcal{H}(\alpha) = -\sum_{i,j \in \{0,1\}} \alpha_{i,j} \lg \alpha_{i,j}$ .

The value  $\text{PE}_P(x, y)$  depends only on  $P$  and the normalized number of occurrences  $\mathbf{NA}(x, y)/n$ .

**DEFINITION 3.3.** For a predicate  $P : \{0, 1\}^d \rightarrow \{0, 1\}$  and a probability distribution  $\alpha \in \Delta^2$ , the probability of equality of  $P$  over  $\alpha$  is

$$\text{PE}_P(\alpha) = \Pr_{(x,y) \sim \alpha^d} [P(x) = P(y)].$$

This allows us to rewrite (1) as

$$M = \sum_{x,y \in \{0,1\}^n} (2^{-1} \text{PE}_P(\mathbf{NA}(x, y)/n))^n$$

In the above expression,  $\mathbf{NA}(x, y)$  takes on values in  $\Delta^2(n)$  depending on the strings  $x$  and  $y$ . For any particular  $\beta \in \Delta^2(n)$ , the number of pairs  $x, y \in \{0, 1\}^n$  satisfying  $\mathbf{NA}(x, y) = \beta$  is equal to  $\binom{n}{\beta_{00}, \beta_{01}, \beta_{10}, \beta_{11}}$ . So we have:

$$M = \sum_{\beta \in \Delta^2(n)} \binom{n}{\beta_{00}, \beta_{01}, \beta_{10}, \beta_{11}} (2^{-1} \text{PE}_P(\beta/n))^n$$

(using Stirling's approximation)

$$\begin{aligned} &\leq \sum_{\beta \in \Delta^2(n)} O((2^{\mathcal{H}(\beta/n)} \cdot 2^{-1} \text{PE}_P(\beta/n))^n) \\ &\leq |\Delta^2(n)| \max_{\alpha \in \Delta^2} O((2^{\mathcal{H}(\alpha)-1} \text{PE}_P(\alpha))^n) \\ &= O(n^3) \max_{\alpha \in \Delta^2} (2^{\mathcal{H}(\alpha)-1} \text{PE}_P(\alpha))^n. \end{aligned}$$

Therefore, in order to prove the lower bound of Theorem 2.5 that  $M \leq n^{O(1)} 2^{2^{-\Omega(d)}n}$ , we have only to show:

$$\forall \alpha \in \Delta^2, \mathcal{H}(\alpha) + \lg \text{PE}_P(\alpha) \leq 1 + 2^{-\Omega(d)}. \quad (2)$$

In sections 3.1 and 3.2, we show that most random predicates and predicates of the form  $P_{h,Q} = x_1 \oplus \dots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  satisfy (2). It is possible in time  $2^{O(d)}$  to test whether a predicate has the form  $P_{h,Q}$ , or whether it has the properties we demand of random predicates in Definition 3.7, so our proof is complete.

### 3.1. Proof of (2) for $P = x_1 \oplus \dots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$

For predicates of the above form, we have

$$\begin{aligned} \text{PE}_P(\alpha) &= \frac{1 + \mathbf{E}[(-1)^{P(x)+P(y)}]}{2} \\ &= \frac{1 + \left( \prod_{i=1}^{d-h} \mathbf{E}[(-1)^{x_i+y_i}] \right) \mathbf{E}[(-1)^{Q(x_{d-h+1}, \dots, x_d)+Q(y_{d-h+1}, \dots, y_d)}]}{2} \\ &\leq \frac{1 + \left| \prod_{i=1}^{d-h} \mathbf{E}[(-1)^{x_i+y_i}] \right|}{2} \\ &= \frac{1 + |\alpha_{00} + \alpha_{11} - \alpha_{10} - \alpha_{01}|^{d-h}}{2}. \end{aligned}$$

Let  $p = \min\{\alpha_{00} + \alpha_{11}, \alpha_{01} + \alpha_{10}\}$ . Then:

$$\begin{aligned} \text{PE}_P(\alpha) &\leq \frac{1 + (1 - 2p)^{d-h}}{2} \\ &\leq \frac{1 + (1 - p)^{d-h}}{2}. \end{aligned}$$

Given  $p$ , the maximum value of  $\mathcal{H}(\alpha)$  is achieved when  $\alpha_{00} = \alpha_{11}$  and  $\alpha_{01} = \alpha_{10}$ ; thus  $\mathcal{H}(\alpha) \leq 1 + \mathcal{H}(p)$ . Therefore, to prove  $\mathcal{H}(\alpha) + \lg \text{PE}_P(\alpha) \leq 1 + 2^{-\Omega(d)}$ , it suffices to show  $\mathcal{H}(p) + \lg(1 + (1 - p)^{d-h}) \leq 1 + 2^{-\Omega(d)}$ . As long as  $d - h = \Omega(d)$ , the following lemma completes the proof with  $\tau = (d - h)/d$ .

**LEMMA 3.4.**  $\forall \tau \in (0, 1], \exists \epsilon > 0, \forall p \in [0, 1] \forall d \geq 1, \mathcal{H}(p) + \lg(1 + (1 - p)^{\tau d}) \leq 1 + 2^{-\epsilon d}$ .

The proof of this lemma can be found in Section 3.3.

### 3.2. Proof of (2) for a Random Predicate $P$

If  $\Delta^2$  were a small finite set, then we could prove (2) as follows. First, show that for any particular  $\alpha \in \Delta^2$ , a random predicate with probability  $1 - \epsilon$  satisfies  $\mathcal{H}(\alpha) + \lg \text{PE}_P(\alpha) \leq 1 + 2^{-\Omega(d)}$ . Then with probability  $1 - \epsilon|\Delta^2|$  this is true for all  $\alpha \in \Delta^2$  simultaneously, which is exactly (2). Since  $\Delta^2$  is an infinite set, this doesn't work, but our proof is similar in spirit: We will devise a small finite set of properties, each of which a random predicate  $P$  satisfies with high probability, then show that (2) follows from these properties.

In order to describe this set of properties, we begin with a new way to measure collisions under a predicate  $P$ . We have already seen  $\text{PE}_P(\alpha)$  where  $\alpha \in \Delta^2$ .

**DEFINITION 3.5.** For  $\beta \in \Delta^2(d)$ , the probability of equality of  $P$  over  $\beta$  is

$$\text{PE}_P(\beta) = \Pr_{(x,y) \sim \mathbf{NA}^{-1}(\beta)} [P(x) = P(y)],$$

where  $\mathbf{NA}^{-1}(\beta)$  denotes the uniform distribution over the set of pairs  $(x, y) \in (\{0, 1\}^d)^2$  satisfying  $\mathbf{NA}(x, y) = \beta$ .

The two definitions of  $\text{PE}_P$  are related by  $\text{PE}_P(\alpha) = \mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)}[\text{PE}_P(\beta)]$ , where  $\text{Mult}(\alpha, d)$  denotes the multinomial distribution which draws  $d$  samples from  $\{0, 1\}^2$  according to the distribution  $\alpha$ .

**DEFINITION 3.6 (ONE-BIT ENTROPY,  $\alpha_{a*}, \alpha_{*a}, \mathcal{H}^*(\alpha)$ ).** Let  $\alpha \in \Delta^2$ .

- For  $a \in \{0, 1\}$ ,  $\alpha_{a*} \stackrel{\text{def}}{=} \alpha(a, 0) + \alpha(a, 1)$  and  $\alpha_{*a} \stackrel{\text{def}}{=} \alpha(0, a) + \alpha(1, a)$ .
- We define the one-bit entropy of  $\alpha$  to be  $\mathcal{H}^*(\alpha) \stackrel{\text{def}}{=} \max\{\mathcal{H}(\alpha_{0*}, \alpha_{1*}), \mathcal{H}(\alpha_{*0}, \alpha_{*1})\}$ .

We now define a small set of properties from which (2) will follow.

**DEFINITION 3.7 (COLLISION-AVERSE PREDICATE).** For  $\delta > 0$  and  $\beta \in \Delta^2(d)$ , we say  $P$  is  $(\delta, \beta)$ -collision averse if

$$\text{PE}_P(\beta) \leq \frac{1}{2} + 2^{-d(\mathcal{H}^*(\beta/d) - \delta)/2}.$$

Let  $E(d)$  (for **E**qual) be the set of  $\beta \in \Delta^2(d)$  such that  $\beta(0, 1) = \beta(1, 0) = 0$ . Notice that if  $(x, y) \in \mathbf{NA}^{-1}(\beta)$ , then  $x = y$  iff  $\beta \in E(d)$ .

If  $P$  is  $(\delta, \beta)$ -collision averse for every  $\beta \in \Delta^2(d) \setminus E(d)$ , we say  $P$  is  $\delta$ -collision averse.

LEMMA 3.8. Fix any  $\delta > 0$  and  $\beta \in \Delta^2(d) \setminus E(d)$ . Choose  $P : \{0, 1\}^d \rightarrow \{0, 1\}$  uniformly at random. Then

$$\Pr[P \text{ is not } (\delta, \beta)\text{-collision averse}] \leq \exp(-\frac{1}{2}2^{\delta d}/\text{poly}(d)).$$

Taking a union bound,

$$\Pr[P \text{ is not } \delta\text{-collision averse}] \leq \exp(-2^{\delta d} - O(\log d)).$$

PROOF OF LEMMA 3.8. Without loss of generality, assume  $\mathcal{H}^*(\beta/d) = \mathcal{H}(\beta_{0^*}/d, \beta_{1^*}/d)$ . Let  $S \subseteq \{0, 1\}^d$  be the support of the marginal distribution on  $x$  when  $(x, y) \sim \mathbf{NA}^{-1}(\beta)$ : that is,  $S$  is the set of strings with  $\beta_{0^*}$  zeroes and  $\beta_{1^*}$  ones.

Pick any  $x \in S$ . If  $P, P' : \{0, 1\}^d \rightarrow \{0, 1\}$  are predicates which differ only at  $x$ , then  $\text{PE}_{P'}(\beta) - \text{PE}_P(\beta) \leq c_x$ , where

$$c_x = \frac{\Pr_{(x', y') \sim \mathbf{NA}^{-1}(\beta)}[x' = x \vee y' = x]}{|\mathcal{S}|} = \frac{2}{\binom{d}{\beta_{0^*}}}.$$

Fix  $P$  arbitrarily on all  $x \notin S$ , but choose the value of  $P$  independently at random for all  $x \in S$ : then  $\mathbf{E}[\text{PE}_P(\beta)] = \frac{1}{2}$ , since  $\beta \notin E(d)$ . By McDiarmid's inequality, for any  $\epsilon$ ,

$$\begin{aligned} \Pr[\text{PE}_P(\beta) > \frac{1}{2} + \epsilon] &\leq \exp\left(-\frac{2\epsilon^2}{\sum_{x \in S} c_x^2}\right) \\ &\leq \exp\left(-\frac{1}{2}\epsilon^2 \binom{d}{\beta_{0^*}}\right) \\ &\leq \exp\left(-\frac{1}{2}\epsilon^2 2^{d\mathcal{H}(\beta_{0^*}/d, \beta_{1^*}/d)} / \text{poly}(d)\right). \end{aligned}$$

To complete the proof, take  $\epsilon = 2^{-d(\mathcal{H}(\beta_{0^*}/d, \beta_{1^*}/d) - \delta)/2}$ .  $\square$

LEMMA 3.9. There exists  $\delta > 0$  such that Equation (2) holds for every  $\delta$ -collision averse predicate. That is, there exist  $\delta, \eta > 0$  and  $D \in \mathbf{N}$  such that whenever  $d > D$  and a  $d$ -ary predicate  $P$  is  $\delta$ -collision averse,

$$\forall \alpha \in \Delta^2, \mathcal{H}(\alpha) + \lg \text{PE}_P(\alpha) \leq 1 + 2^{-\eta d}.$$

PROOF. Let  $\alpha \in \Delta^2$ . By the concavity of the logarithm function,

$$\lg \text{PE}_P(\alpha) \leq \lg \xi + \frac{1}{\xi \ln 2} (\text{PE}_P(\alpha) - \xi)$$

where  $\xi$  will be determined later. Since  $\text{PE}_P(\alpha) = \mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)}[\text{PE}_P(\beta)]$ , we have

$$\lg \text{PE}_P(\alpha) \leq \lg \xi + \frac{1}{\xi \ln 2} \left( \mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)} \text{PE}_P(\beta) - \xi \right). \quad (3)$$

We assume  $P$  is  $\delta$ -collision averse, where  $\delta$  will be determined later. That means that whenever  $\beta(0, 1) + \beta(1, 0) > 0$ , it is the case that  $\text{PE}_P(\beta) \leq \frac{1}{2} + 2^{-d(\mathcal{H}^*(\beta/d) - \delta)/2}$ . So, if we let  $E(d) = \{\beta : \beta(0, 1) = \beta(1, 0) = 0\}$  and  $\gamma = \Pr_{\beta \sim \text{Mult}(\alpha, d)}[\beta \in E(d)]$ , we have:

$$\begin{aligned} \mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)} \text{PE}_P(\beta) &\leq \gamma + (1 - \gamma) \cdot \mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)} [\min\{1, \frac{1}{2} + 2^{-d(\mathcal{H}^*(\beta/d) - \delta)/2}\} | \beta \notin E(d)] \\ &= \frac{1+\gamma}{2} + (1 - \gamma) \cdot \mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)} [\min\{\frac{1}{2}, 2^{-d(\mathcal{H}^*(\beta/d) - \delta)/2}\} | \beta \notin E(d)] \\ &\leq \frac{1+\gamma}{2} + \mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)} [\min\{\frac{1}{2}, 2^{-d(\mathcal{H}^*(\beta/d) - \delta)/2}\}]. \end{aligned}$$

Whenever a random variable  $X$  is bounded above by 1, Markov's inequality gives  $\mathbf{E}[X] \leq a + \Pr[X > a]$  for all  $a \geq 0$ . Taking  $a = 2^{-\delta d/2}$  where the value of  $\delta$  still has to be determined,

$$\mathbf{E}_{\beta \sim \text{Mult}(\alpha, d)} \text{PE}_P(\beta) \leq \frac{1+\gamma}{2} + 2^{-\delta d/2} + \Pr_{\beta \sim \text{Mult}(\alpha, d)}[\mathcal{H}^*(\beta/d) < 2\delta].$$

Now, substitute back in to (3) taking  $\xi = \frac{1+\gamma}{2}$ :

$$\begin{aligned} \lg \text{PE}_P(\alpha) &\leq \lg \frac{1+\gamma}{2} + \frac{2}{(1+\gamma) \ln 2} \left( 2^{-\delta d/2} + \Pr_{\beta \sim \text{Mult}(\alpha, d)}[\mathcal{H}^*(\beta/d) < 2\delta] \right) \\ &\leq \lg \frac{1+\gamma}{2} + 3 \left( 2^{-\delta d/2} + \Pr_{\beta \sim \text{Mult}(\alpha, d)}[\mathcal{H}^*(\beta/d) < 2\delta] \right). \end{aligned}$$

Since  $\mathcal{H}^*(\beta/d) \geq \mathcal{H}(\beta_{0^*}/d)$ , we have:

$$\lg \text{PE}_P(\alpha) \leq \lg \frac{1+\gamma}{2} + 3 \left( 2^{-\delta d/2} + \Pr_{\beta \sim \text{Mult}(\alpha, d)}[\mathcal{H}(\beta_{0^*}/d) < 2\delta] \right).$$

Sampling  $\beta \sim \text{Mult}(\alpha, d)$  and looking at  $\beta_{0^*}$  is the same as sampling  $k \sim \text{Binom}(\alpha_{0^*}, d)$ . So we can rewrite the above as:

$$\lg \text{PE}_P(\alpha) \leq \lg \frac{1+\gamma}{2} + 3 \left( 2^{-\delta d/2} + \Pr_{k \sim \text{Binom}(\alpha_{0^*}, d)}[\mathcal{H}(k/d) < 2\delta] \right). \quad (4)$$

Since  $\lg \text{PE}_P(\alpha) \leq 0$ , the claim of the lemma follows when  $\mathcal{H}(\alpha) \leq 1$ ; so henceforth we assume  $\mathcal{H}(\alpha) \geq 1$ , and hence  $\mathcal{H}^*(\alpha) \geq 1/2$ . We may further assume without loss of generality that  $\mathcal{H}(\alpha_{0^*}) \geq 1/2$ . Let  $p_0 \in (0, \frac{1}{2})$  be the unique number satisfying  $\mathcal{H}(p_0) = \frac{1}{2}$ ; we know  $\alpha_{0^*} \in [p_0, 1 - p_0]$ . We now introduce a technical lemma which is proved in Section 3.3:

**LEMMA 3.10.** *For every  $p_0 \in (0, \frac{1}{2}]$ , there exists  $\delta > 0$  such that for all sufficiently large  $d \in \mathbf{N}$ ,*

$$\forall p \in [p_0, 1 - p_0], \quad \Pr_{k \sim \text{Binom}(p, d)}[\mathcal{H}(k/d) < 2\delta] + 2^{-\delta d/2} \leq 2^{-\delta d/3}.$$

Apply this lemma to get  $\delta > 0$ , and substitute back into (4):

$$\lg \text{PE}_P(\alpha) \leq \lg(1 + \gamma) - 1 + 3 \cdot 2^{-\delta d/3}.$$

Now, the aim of this Lemma is to bound  $\mathcal{H}(\alpha) + \lg \text{PE}_P(\alpha)$ . We have so far:

$$\begin{aligned} \mathcal{H}(\alpha) + \lg \text{PE}_P(\alpha) &\leq \mathcal{H}(\alpha) + \lg(1 + \gamma) - 1 + 3 \cdot 2^{-\delta d/3} \\ &\leq \mathcal{H}(\alpha_{00} + \alpha_{11}) + \lg(1 + \gamma) + 3 \cdot 2^{-\delta d/3}. \end{aligned}$$

Now,  $\gamma = \Pr[\beta(0, 1) = \beta(1, 0) = 0] = (\alpha_{00} + \alpha_{11})^d$ . Apply Lemma 3.4, taking  $\tau = 1$  and  $p = 1 - (\alpha_{00} + \alpha_{11})$ . Then:

$$\mathcal{H}(\alpha) + \lg \text{PE}_P(\alpha) \leq 1 + 2^{-\epsilon d} + 3 \cdot 2^{-\delta d/3}.$$


Take  $\eta < \min\{\epsilon, \delta/3\}$  and  $d$  sufficiently large that  $2^{-\eta d} > 2^{-\epsilon d} + 3 \cdot 2^{-\delta d/3}$  to complete the proof.  $\square$

### 3.3. Proof of Lemmas 3.4 and 3.10

*Proof of Lemma 3.4.* Assume  $\tau \in (0, 1]$  is given. First we show that we can choose positive  $D$  and  $\epsilon'$  such that

$$\forall p \in [0, 1], \forall d > D, \mathcal{H}(p) + \lg(1 + (1-p)^{\tau d}) \leq 1 + 2^{-\epsilon' d}. \quad (5)$$

We prove this by considering four possible cases for the value of  $p$ , namely,  $p \in (\epsilon_1, 1]$ ,  $p \in (\epsilon_2/d, \epsilon_1]$ ,  $p \in (2^{-\epsilon_3 d}, \epsilon_2/d]$ ,  $p \in [0, 2^{-\epsilon_3 d}]$ , where  $\epsilon_1, \epsilon_2, \epsilon_3$  are positive constants to be chosen. We will choose the numbers  $D$  and  $\epsilon', \epsilon_1, \epsilon_2, \epsilon_3$  as we go along, but according to the following dependency graph:



— Case 1:  $p > \epsilon_1$ . Then

$$\mathcal{H}(p) + \lg(1 + (1-p)^{\tau d}) \leq 1 + (1-\epsilon_1)^{\tau d} \lg e \leq 1 + 2^{-\epsilon' d},$$

for  $\epsilon_1 < 1$ ,  $\epsilon' \leq -\frac{1}{2}\tau \lg(1-\epsilon_1)$ ,  $d > D \geq -2 \lg \lg e / (\tau \lg(1-\epsilon_1))$ .

For the remaining three cases,  $p$  is small. Using the Taylor expansion of  $\lg$  around 2, we get

$$\lg(1 + (1-p)^{\tau d}) \leq 1 + \frac{(1-p)^{\tau d} - 1}{2 \ln 2} \leq 1 + \frac{e^{-\tau p d} - 1}{2 \ln 2}.$$

— Case 2:  $p \in (\epsilon_2/d, \epsilon_1]$ . Then

$$\mathcal{H}(p) + \lg(1 + (1-p)^{\tau d}) \leq \mathcal{H}(\epsilon_1) + 1 + \frac{e^{-\tau \epsilon_2} - 1}{2 \ln 2} \leq 1,$$

if we choose  $\epsilon_1$  small enough that  $\epsilon_1 \leq 1/2$  and  $\mathcal{H}(\epsilon_1) \leq (1 - e^{-\tau \epsilon_2}) / (2 \ln 2)$ .

For the remaining two cases we fix  $\epsilon_2 = (2\tau)^{-1}$ . Now,  $\tau p d \leq \frac{1}{2}$ , and we have the approximation

$$\mathcal{H}(p) + 1 + \frac{e^{-\tau p d} - 1}{2 \ln 2} \leq (p \lg(1/p) + 2p) + 1 - \frac{\tau p d}{4 \ln 2} = 1 + p \left( \lg(1/p) - \frac{\tau}{4 \ln 2} d + 2 \right).$$

— Case 3:  $p \in (2^{-\epsilon_3 d}, \epsilon_2/d]$ .

For  $\epsilon_3 < \frac{\tau}{4 \ln 2}$  and  $d > D$  for sufficiently large  $D$  (depending on  $\epsilon_3$ ):  $\lg(1/p) - \frac{\tau}{4 \ln 2} d + 2 < 0$ .

— Case 4:  $p \leq 2^{-\epsilon_3 d}$ .

For  $\epsilon' \leq \frac{1}{2}\epsilon_3$  and  $d > D$  for sufficiently large  $D$  (depending on  $\epsilon_3$ ):  $p \lg(1/p) \leq \epsilon_3 d 2^{-\epsilon_3 d} \leq 2^{-\epsilon' d}$ .

We have proved (5). It remains to prove the lemma for  $d \in [1, D]$ . Let  $f(p, d) = \mathcal{H}(p) + \lg(1 + (1-p)^{\tau d})$ . Since  $f$  is a continuous function on the compact set  $[0, 1] \times [1, D]$ , it achieves a finite maximum  $M = f(p_*, d_*)$  on this set. It is easy to see that  $M \in (1, 2)$ . Let  $\epsilon = \min\{\epsilon', -D^{-1} \lg(M-1)\}$ . Then for  $d \in [1, D]$ ,  $f(p, d) \leq M \leq 1 + 2^{-\epsilon d}$ , and for  $d \in (D, \infty)$ ,  $f(p, d) \leq 1 + 2^{-\epsilon' d} \leq 1 + 2^{-\epsilon d}$ .  $\square$

*Proof of Lemma 3.10.* Let  $D_{KL}$  denote the Kullback-Leibler divergence

$$D_{KL}(q\|p) = q \lg \frac{q}{p} + (1-q) \lg \frac{1-q}{1-p}.$$

Fix  $\lambda > 0$  to be small enough that  $\lambda < 1/2$  and for any  $p \in [p_0, 1 - p_0]$ ,

$$D_{KL}(\lambda\|p) > \mathcal{H}(\lambda).$$

Now, choose any  $p \in [p_0, 1 - p_0]$ .

$$\Pr_{k \sim \text{Binom}(p,d)}[\mathcal{H}(k/d) < \mathcal{H}(\lambda)] = \Pr[k/d < \lambda] + \Pr[k/d > 1 - \lambda]$$

$$\text{(Without loss of generality, assume } p \leq \frac{1}{2}.) \quad \leq 2 \Pr[k/d < \lambda]$$

$$\text{(Apply Chernoff's bound.)} \quad \leq 2 \exp(-D_{KL}(\lambda\|p)d)$$

$$< 2 \exp(-\mathcal{H}(\lambda)d).$$

Complete the proof by taking  $\delta = \mathcal{H}(\lambda)/2$  and taking  $d$  to be sufficiently large that  $2 \exp(-\mathcal{H}(\lambda)d) < 2^{-\delta d/3} - 2^{-\delta d/2}$ .  $\square$

#### 4. LOCALLY CONSISTENT PARTIAL ASSIGNMENT

In this section, we assume we are given an instance of Goldreich's function  $f = f_{P,G} : \{0, 1\}^n \rightarrow \{0, 1\}^m$  together with  $b \in \{0, 1\}^m$ . We want to analyze a backtracking algorithm  $\mathcal{A}$  that tries to find an element in the preimage  $f^{-1}(b)$ . A crucial concept in this analysis will be that of a locally consistent partial assignment. In order to introduce this concept, we will introduce some preliminary concepts.

**DEFINITION 4.1 (PARTIAL ASSIGNMENT).** A partial assignment is a function  $\rho : [n] \rightarrow \{0, 1, *\}$ . Its set of fixed variables is  $\text{Vars}(\rho) = \rho^{-1}(\{0, 1\})$ . Its set of free variables is  $\rho^{-1}(\{*\})$ . Its size is defined to be  $|\rho| = |\text{Vars}(\rho)|$ . Given  $f : \{0, 1\}^n \rightarrow \{0, 1\}^m$ , the restriction of  $f$  by  $\rho$ , denoted  $f|_\rho$ , is the function obtained by fixing the variables in  $\text{Vars}(\rho)$  and allowing the rest of the variables of  $f$  to vary.

For a partial assignment  $\rho$ , an index  $j \in [n]$ , and a value  $a \in \{0, 1\}$ , we define the partial truth assignment  $\rho[x_j \leftarrow a]$  by

$$\rho[x_j \leftarrow a](i) = \begin{cases} a, & i = j; \\ \rho(i), & i \neq j. \end{cases}$$

**DEFINITION 4.2 (BOUNDARY, NEIGHBORHOOD, AND EXPANSION).** Let  $G \in [n]^{m \times d}$  be a bipartite graph as in Definition 2.1. Let  $I \subseteq R$  be a subset of vertices on the right. Its neighborhood  $\Gamma(I) \subseteq L$  is the set of all nodes adjacent to nodes in  $I$ . For  $i \in I$ , the boundary of  $i$  in  $I$ , denoted  $\partial_I i$ , is the set of nodes in  $L$  with one edge to  $i$  but no other edges to  $I$ . The boundary of  $I$ , denoted  $\partial I$ , is the set of all nodes  $j \in L$  such that there is exactly one edge from  $j$  to  $I$ . Equivalently,  $\partial I = \bigcup_{i \in I} \partial_I i$ .

$G$  is an  $(r, c)$ -boundary expander if for all  $I \subseteq R$  such that  $|I| \leq r$ , we have  $|\partial I| \geq c|I|$ .

**DEFINITION 4.3 (CLOSURE).** Let  $G \in [n]^{m \times d}$  be a bipartite graph as in Definition 2.1. Assume  $G$  is an  $(r, c)$ -boundary expander. Fix a subset of input nodes  $J \subseteq L$ . We say a subset of output nodes  $I \subseteq R$  of size  $|I| \leq r/2$  is a closure for  $J$  if the subgraph of  $G$  obtained by deleting nodes in  $J \cup \Gamma(I)$  and nodes in  $I$  is an  $(r/2, c/2)$ -boundary expander.

Note that a closure for a set of left-nodes is a set of right-nodes.

**DEFINITION 4.4 (LOCALLY CONSISTENT PARTIAL ASSIGNMENT).** Let  $f$  be Goldreich's function for graph  $G$  and predicate  $P$ . Let  $b \in \{0, 1\}^m$  and let  $\rho$  be a partial


assignment. For a set of output nodes  $I \subseteq R$ , we say  $\rho$  is consistent with  $I$  if  $\rho$  can be extended to some  $x' \in \{0, 1\}^n$  such that  $f(x')_I = b_I$ . We say  $\rho$  is locally consistent if there exists a closure  $I$  for  $\text{Vars}(\rho)$  such that  $\rho$  is consistent with  $I$ . We say  $\rho$  is globally consistent if  $\rho$  is consistent with  $R$ .

#### 4.1. Backtracking Trees and Resolution Proofs

**DEFINITION 4.5 (BACKTRACKING TREE).** *The running of a backtracking algorithm  $\mathcal{A}$  in finding a solution to the equation  $f_{P,G}(x) = b$  can be modeled by a backtracking tree. Each node of the backtracking tree is labeled by a partial assignment  $\rho : [n] \rightarrow \{0, 1, *\}$ , where  $\rho_j = *$  means variable  $x_j$  is free and  $\rho_j \neq *$  means variable  $x_j$  is assigned the value  $\rho_j$ . We measure the running time of algorithm  $\mathcal{A}$  in terms of the number of nodes in its backtracking tree.*

*The root of the backtracking tree is labeled by the empty partial assignment  $*^n$ . If at a step of the backtracking, the current partial assignment is  $\rho$  and algorithm  $\mathcal{A}$  chooses the assignment  $x_j \leftarrow a$  where  $x_j$  is a free variable and  $a \in \{0, 1\}$ , then the left child of the current node is labeled by  $\rho[x_j \leftarrow a]$ . If the current node has a right child, the label of this right child is  $\rho[x_j \leftarrow 1 - a]$ .*

For example, here is part of a backtracking tree. One of the nodes is boxed. The label of that node is a partial assignment that assigns values 0, 1, 0 to variables  $x_5$ ,  $x_7$ , and  $x_8$  respectively.



In this subsection, we motivate the definition of locally consistent partial assignments by showing that a backtracking subtree with a root that is labeled by a locally consistent but globally inconsistent partial assignment has exponential size.

**DEFINITION 4.6 (TREE-LIKE RESOLUTION PROOF).** *If  $C = a \vee D$  and  $C' = \neg a \vee D'$  are two clauses each consisting of an OR of literals,  $C$  and  $C'$  together imply  $D \vee D'$ . In this case,  $D \vee D'$  is called the resolution of  $C$  and  $C'$ . Let  $\Phi$  be a CNF formula. A resolution proof for refuting  $\Phi$  is a sequence of clauses  $C_1, C_2, \dots, C_l$  where  $C_1$  is the empty clause, and for  $i = 1, \dots, l$ ,*

- either  $C_i$  is a clause appearing in  $\Phi$ ,
- or  $C_i$  is the resolution of two clauses that appear before  $C_i$  in the sequence.

*If each clause in the sequence (except the last clause  $C_l$ ) is used exactly once to imply a later clause in the sequence through a resolution, then the resolution proof is called*



tree-like. The length of the resolution proof is  $l$ . The width of the resolution proof is the width of the maximum-width clause among  $C_1, \dots, C_l$ .

LEMMA 4.7. (Refer to for example [Iwama and Miyazaki 1999, Proposition 1]) Let  $\rho$  be the label of the root of a subtree of a backtracking tree for finding a solution  $x$  to  $f_{P,G}(x) = b$ . One can express  $f_{P,G}(x) = b$  by a CNF formula  $\Phi$  by translating each constraint  $P(x_{G_{i,1}}, \dots, x_{G_{i,d}}) = b_i$  into  $\leq 2^d$  clauses of width  $d$ . Define  $\Phi|_\rho$  to be the CNF formula which is the restriction of  $\Phi$  by  $\rho$ . If no solution  $x$  is found in this subtree, then  $\Phi|_\rho$  has a tree-like resolution proof of length no bigger than the number of nodes in the subtree.

PROOF. To each node labeled  $\rho'$  in this subtree, we can in the following recursive way associate a clause  $C_{\rho'}$  over the free variables of  $\rho$  such that  $C_{\rho'}$  is false under the partial assignment  $\rho'$ :

- For a leaf node labeled  $\rho'$ , one of the constraints  $P(x_{G_{i,1}}, \dots, x_{G_{i,d}}) \neq b_i$  is not satisfiable under  $\rho'$ . Therefore at least one clause  $C_{\rho'}$  exists in  $\Phi|_\rho$  that is not satisfiable under  $\rho'$ .
- For a node labeled  $\rho'$  with left and right children  $\rho^l = \rho'[x_j \leftarrow a]$  and  $\rho^r = \rho'[x_j \leftarrow 1 - a]$ , if either of the two clauses  $C_{\rho^l}$  or  $C_{\rho^r}$  does not include the variable  $x_j$ , then choose that clause as  $C_{\rho'}$ , otherwise let  $C_{\rho'}$  be the resolution of  $C_{\rho^l}$  and  $C_{\rho^r}$ .

In this way, the labels of a postorder tree traversal of the subtree rooted at  $\rho$  can give a tree-like resolution proof for refuting  $\Phi|_\rho$ .  $\square$

DEFINITION 4.8 (ROBUST PREDICATE). Let  $0 \leq h < d$  be an integer. The predicate  $P : \{0, 1\}^d \rightarrow \{0, 1\}$  is  $h$ -robust if after any partial assignment of values to the input variables of  $P$  that lets  $> h$  of the input variables of  $P$  be free, the predicate  $P$  can still take both of the two possible values of 0 and 1 as its value. For example, the predicate that sums all its inputs modulo 2 is 0-robust.

THEOREM 4.9. [Ben-Sasson and Wigderson 2001] The length of any tree-like resolution refutation of a CNF formula  $\Psi$  is at least  $2^{w-w_\Psi}$ , where  $w$  is the minimal width of a resolution refutation of  $\Psi$ , and  $w_\Psi$  is the maximal width of a clause in  $\Psi$ .

LEMMA 4.10. Consider running a backtracking algorithm for solving  $f_{P,G}(x) = b$ . Assume that the algorithm reaches a locally consistent but globally inconsistent partial assignment  $\rho$ . Assume  $P$  is  $h$ -robust. Then in the backtracking tree, the subtree rooted at  $\rho$  has size at least  $2^{(c/2-h)r/4-d}$ .

PROOF. (Our proof follows the proof of [Alekhovich et al. 2005, Lemma 8], which in turn uses the Ben-Sasson-Wigderson measure [2001].) Let  $\Phi|_\rho$  be as in Lemma 4.7. By Theorem 4.9, it suffices to show that every resolution refutation of  $\Phi|_\rho$  has width at least  $w \stackrel{\text{def}}{=} (c/2 - h)r/4$ .

Since  $\rho$  is locally consistent, there exists a closure  $I$  for  $\text{Vars}(\rho)$  and  $\rho$  can be extended to some  $x' \in \{0, 1\}^n$  such that  $f(x')_I = b_I$ . Let  $J = \text{Vars}(\rho) \cup \Gamma(I)$ . We will prove the stronger statement that every resolution refutation of  $\Phi_{[x_J=x'_J]}$  has width at least  $w$ .

For a clause  $C$  on the variables  $x_{L \setminus J}$  and a set  $I' \subseteq R \setminus I$ , we say  $I'$  implies  $C$  if for every  $x$  such that  $(f(x)_{I'} = b_{I'} \wedge x_J = x'_J)$ , the clause  $C$  is satisfied by  $x$ . We define the measure of  $C$  to be

$$\mu(C) = \min\{|I'| : I' \subseteq R \setminus I, \text{ and } I' \text{ implies } C\}.$$

Since  $\rho$  is globally inconsistent, this measure is well-defined. Assume  $\mu(C) \leq r/2$ , and let  $I'$  be a smallest subset of  $R \setminus I$  which implies  $C$ . No vertex  $i \in I'$  contains more than

$h$  neighbors in  $\partial I' \setminus J$  that do not appear in  $C$ , since otherwise, by the  $h$ -robustness of the predicate  $P$ , then  $I' \setminus \{i\}$  would also imply  $C$ . Since  $I$  is a closure for  $\text{Vars}(\rho)$ , we know  $|\partial I' \setminus J| \geq c|I'|/2$ , so  $C$  consists of at least  $(c/2 - h)\mu(C)$  variables. Thus we have proved:

$$\text{For any clause } C, \mu(C) \text{ is either } \leq \frac{\text{width}(C)}{c/2 - h} \text{ or } > r/2. \quad (\#)$$

We have:

- (1)  $\mu(C) = 1$  for any clause  $C$  in the CNF formula  $\Phi_{[x_J=x'_J]}$ .
- (2)  $\mu(C) > r/2$  for the empty clause  $C = \text{False}$  (because of (#) and because the empty clause has positive measure  $\mu(C)$ .)
- (3)  $\mu$  is subadditive: If  $C_2$  is the resolution of  $C_0$  and  $C_1$ , then  $\mu(C_2) \leq \mu(C_0) + \mu(C_1)$ , because whenever  $I'_0$  implies  $C_0$  and  $I'_1$  implies  $C_1$ , it follows that  $I'_0 \cup I'_1$  implies  $C_2$ .

Putting 1, 2 and 3 together, we find that every resolution refutation of  $\Phi_{[x_J=x'_J]}$  contains a clause  $C$  whose measure is in the range  $(r/4, r/2]$ . By (#), the width of  $C$  is at least  $w = (c/2 - h)r/4$ , which completes the proof.  $\square$

#### 4.2. Clever Backtracking

For the analysis of drunk and myopic backtracking algorithms, we consider the left-most node in the backtracking tree among nodes labeled by locally consistent partial assignments. In order to argue about this particular partial assignment more easily, we modify the backtracking algorithm into a so-called *clever* backtracking algorithm such that this particular partial assignment appears on the left-most branch of the tree.

**DEFINITION 4.11 (LOCALLY FORCED ASSIGNMENT).** *Let  $f$  be Goldreich's function, let  $b \in \{0, 1\}^m$ , let  $\rho$  be a partial assignment, and let  $j \in [n] \setminus \text{Vars}(\rho)$ . We say an assignment  $x_j \leftarrow a$  is locally forced if  $\rho[x_j \leftarrow a]$  is locally consistent but  $\rho[x_j \leftarrow 1 - a]$  is not. Otherwise we say the assignment is locally unforced.*

**DEFINITION 4.12 (CLEVER BACKTRACKING).** *Let  $\mathcal{A}$  be a backtracking algorithm for finding a solution  $x$  to  $f_{P,G}(x) = b$ . The algorithm  $\mathcal{A}$  is clever if whenever the current partial assignment is  $\rho$  and the assignment  $x_j \leftarrow 1 - a$  is locally forced, the algorithm does not first try the assignment  $x_j \leftarrow a$ .*

*Given a backtracking algorithm  $\mathcal{A}$ , we can give a clever version  $\mathcal{C}(\mathcal{A})$  of  $\mathcal{A}$  as follows:  $\mathcal{C}(\mathcal{A})$  is similar to  $\mathcal{A}$  except that at each step when the current partial assignment is  $\rho$ , if  $\mathcal{A}$  chooses the assignment  $x_j \leftarrow a$  to try first, the clever version  $\mathcal{C}(\mathcal{A})$  checks whether  $x_j \leftarrow 1 - a$  is locally forced. If  $x_j \leftarrow 1 - a$  is locally forced,  $\mathcal{C}(\mathcal{A})$  tries the assignment  $x_j \leftarrow 1 - a$  first instead of  $x_j \leftarrow a$ .*

It is clear that the running time of the clever version of any backtracking algorithm  $\mathcal{A}$  is as good as the algorithm  $\mathcal{A}$  itself, since the clever algorithm only delays searching those subtrees that we are sure do not contain any solution in the preimage  $f^{-1}(b)$ .

Here is our main lemma about clever backtracking algorithms. We will defer its proof to the next section when we have developed the necessary tools.

**LEMMA 4.13.** *Consider a clever backtracking algorithm  $\mathcal{A}$ . Assume the predicate  $P$  is  $h$ -robust for  $h < c/2 - 1$ . The algorithm will make at least  $\lfloor cr/4 \rfloor$  locally unforced assignments on its leftmost branch. Furthermore, the partial assignment  $\rho$  obtained on this branch after  $\lfloor cr/4 \rfloor$  locally unforced assignments is locally consistent.*

#### 4.3. Some Properties of Closures and Consistency

**LEMMA 4.14.** *If  $I \subseteq R$  is a closure for  $J \subseteq L$ , then  $I$  is a closure also for  $J \cup \Gamma(I)$ .*

PROOF. The statement follows directly from the definition of closure.  $\square$

LEMMA 4.15. Analogous to [Alekhovich et al. 2005, Lemma 6].

Let  $J \subseteq L$  have size  $|J| \leq cr/4$ . Then there exists a closure  $C$  for  $J$  such that  $|C| \leq 2c^{-1}|J|$ .

PROOF. Call  $I \subseteq R$  *nonexpanding* if  $|\partial I \setminus J| \leq c|I|/2$ . For a nonexpanding  $I$  we have  $|\partial I| \leq c|I|/2 + |J|$ . If, furthermore,  $|I| \leq r$ , by the  $(r, c)$ -boundary-expansion of  $G$  we have  $|\partial I| \geq c|I|$ , so  $|I| \leq 2c^{-1}|J| \leq r/2$ . Therefore a nonexpanding  $I \subseteq R$  has either  $> r$  vertices or  $\leq r/2$  vertices.

Let  $C$  be a largest nonexpanding set with  $\leq r/2$  vertices. ( $C$  might be empty.) We claim that  $C$  is a closure for  $J$ . Indeed, let  $S$  be any subset of  $R \setminus C$  with  $\leq r/2$  vertices. It suffices to show that  $|\partial S \setminus (J \cup \Gamma(C))| \geq c|S|/2$ . Suppose otherwise: then  $S$  is nonempty, and also  $|\partial(C \cup S) \setminus J| \leq |\partial C \setminus J| + |\partial S \setminus (J \cup \Gamma(C))| < c|C|/2 + c|S|/2 = c|C \cup S|/2$ . Then  $C \cup S$  is a nonexpanding set with  $\leq r$  vertices, and therefore  $\leq r/2$  vertices. This contradicts our assumption that  $C$  was a largest nonexpanding set with  $\leq r/2$  vertices.

Finally, we showed at the start of the proof that  $|C| \leq 2c^{-1}|J|$ .  $\square$

LEMMA 4.16. Analogous to [Alekhovich et al. 2005, Lemma 7].

A partial assignment  $\rho$  is consistent with all  $I \subseteq R$  having size  $|I| \leq r/2$  if  $\rho$  is locally consistent and  $P$  is  $h$ -robust for  $h < c/2$ . The same is true about  $\rho$  if  $\rho$  is consistent with a closure  $C$  for  $\text{Vars}(\rho) \setminus A$  where  $A \subseteq \text{Vars}(\rho)$  and  $P$  is  $h$ -robust for  $h < c/2 - |A|$ .

PROOF. (We only prove the second statement of the Lemma: The statement about locally consistent  $\rho$  follows from the second statement by fixing  $A = \emptyset$ .)

Let  $I$  be a smallest set such that  $\rho$  is not consistent with  $I$ . Assume that, contrary to the statement of the lemma,  $|I| \leq r/2$ . We know  $I' = I \setminus C$  is non-empty. Define  $J = \text{Vars}(\rho) \cup \Gamma(C)$ . Since  $C$  is a closure for  $\text{Vars}(\rho) \setminus A$ , we have  $|\partial I' \setminus J| \geq c|I'|/2 - |A|$ . In particular, there must be some  $i \in I'$  with  $|\partial_{I'} i \setminus J| \geq \lceil c/2 - |A| \rceil$ .

Since  $I$  is a smallest set with which  $\rho$  is not consistent,  $\rho$  is consistent with  $I \setminus \{i\}$ . So extend  $\rho$  to a partial assignment  $x'$  which satisfies  $(f(x'))_{I \setminus \{i\}} = b_{I \setminus \{i\}}$ . Since  $P$  is a  $\lceil c/2 - |A| - 1 \rceil$ -robust predicate, we can modify input bits in the set  $|\partial_{I'} i \setminus J|$  and leave all other input bits the same to produce an input  $x''$  such that  $(f(x''))_i = b_i$ . Since  $x''$  is equal to  $x'$  on every input bit in  $\Gamma(I \setminus \{i\})$ , we have  $(f(x''))_I = b_I$ . This contradicts the assumption that  $\rho$  is not consistent with  $I$ .  $\square$

We are now ready to prove Lemma 4.13.

PROOF OF LEMMA 4.13. Consider the running of clever algorithm  $\mathcal{A}$  for  $s$  steps on its leftmost branch of its backtracking tree. Let  $\rho^0, \dots, \rho^s$ , where  $|\text{Vars}(\rho^i)| = i$ , be the sequence of the partial assignments appearing on the nodes of this leftmost branch. Let  $F_s$  be the set of indices  $j \in \text{Vars}(\rho^s)$  of variables  $x_j$  whose assignment by  $\mathcal{A}$  during this branch was locally forced. Let  $U_s = \text{Vars}(\rho^s) \setminus F_s$ .

We first prove by induction on  $s$  the following claim:

If  $C$  is a closure for  $U_s$  then  $F_s \subseteq \Gamma(C)$ , and thus by Lemma 4.14  $C$  is a closure for  $\text{Vars}(\rho^s)$ .

The base case  $s = 0$  is obvious. Now assume the claim is true for  $s - 1$ , and we want to prove the claim for  $s$ . Since  $C$  is a closure for  $U_s$ , it is also a closure for the smaller set  $U_{s-1}$ , hence  $F_{s-1} \subseteq \Gamma(C)$ . If  $F_{s-1} = F_s$ , we are done with the proof of the claim. Otherwise,  $\rho^s = \rho^{s-1}[x_j \leftarrow a]$ , where  $\rho^s$  is locally consistent but  $\rho^{s-1}[x_j \leftarrow 1 - a]$  is not locally consistent.  $\rho^s$  is consistent with a closure  $I$  for  $\text{Vars}(\rho^s)$ . Thus, by Lemma 4.16,  $\rho^s$  is consistent with  $C$ . If  $j \in \Gamma(C)$ , we are done with the proof of the claim. Otherwise,  $\rho' := \rho^{s-1}[x_j \leftarrow 1 - a]$  is also consistent with  $C$ . By an application of Lemma 4.16

with  $A = \{j\}$ , we know  $\rho'$  is consistent with  $I$  which is also a closure for  $\text{Vars}(\rho')$ . This contradicts the fact that  $\rho'$  is not locally consistent, proving the claim.

In order to prove the Lemma itself, it suffices to prove the following two facts:

- (1) If  $|U_s| \leq \lfloor cr/4 \rfloor$ , there exists a closure  $C$  for  $\text{Vars}(\rho^s)$  (and therefore  $s < n$ ).
- (2) If  $|U_{s-1}| < \lfloor cr/4 \rfloor$  and  $\rho^{s-1}$  is locally consistent, then  $\rho^s$  is locally consistent.

To prove the first fact, notice that by Lemma 4.15 there exists a closure  $C$  for  $U_s$ . By the claim we proved earlier,  $C$  is also a closure for  $\text{Vars}(\rho^s)$ .

To prove the second fact, let  $C$  be the closure for  $\text{Vars}(\rho^s)$  which is guaranteed to exist by the first fact. If  $\rho^s$  is not locally consistent, neither is  $\rho^{s-1}[x_j \leftarrow 1 - a]$  locally consistent because  $\mathcal{A}$  is clever. Therefore, both  $\rho^{s-1}[x_j \leftarrow a]$  and  $\rho^{s-1}[x_j \leftarrow 1 - a]$  are not consistent with  $C$ . But this exactly means  $\rho^{s-1}$  is not consistent with  $C$ ; hence by Lemma 4.16,  $\rho^{s-1}$  is not locally consistent. This contradiction proves the second fact.  $\square$

## 5. DRUNK BACKTRACKING ALGORITHMS

The goal of this section is to prove Theorem 2.8.

### 5.1. Probability of Correct Guess

Notice that the clever version  $\mathcal{C}(\mathcal{A})$  of a drunk algorithm  $\mathcal{A}$  is also randomized whenever it makes a locally unforced assignment.

**LEMMA 5.1 (MAIN DRUNK LEMMA).** *Let  $\mathcal{A}$  be a drunk backtracking algorithm for inverting Goldreich's function. Assume that we are guaranteed that  $\mathcal{C}(\mathcal{A})$  makes at least  $s'$  locally unforced assignments on the left-most branch of its backtracking tree as e.g. by Lemma 4.13. Choose  $x' \in \{0, 1\}^n$  and let  $b = f_{P,G}(x')$ . When  $b$  is given as input to  $\mathcal{C}(\mathcal{A})$ , let  $\rho^{s'}$  be the resulting partial assignment on the left-most branch after  $s'$  locally unforced assignments. The probability, over the randomness of algorithm  $\mathcal{C}(\mathcal{A})$ , that  $\rho^{s'}$  can be extended to  $x'$  is exactly  $2^{-s'}$ .*

**PROOF.** We shall prove this by induction on  $s'$ . The statement for the base case  $s' = 0$  is clear:  $*^n$  can always be extended to  $x$ .

For  $s' \geq 1$ , let  $\rho_{\text{bef}}^{s'}$  be the partial assignment just before the  $s'$ -th non-forced assignment is made. Since  $\rho_{\text{bef}}^{s'}$  is obtained from  $\rho^{s'-1}$  by adding some locally forced assignments, we know that  $\rho_{\text{bef}}^{s'}$  can be extended to  $x'$  if and only if  $\rho^{s'-1}$  can be.

Furthermore, to get from  $\rho_{\text{bef}}^{s'}$  to  $\rho^{s'}$ , the drunk algorithm  $\mathcal{A}$  makes a choice  $x_j \leftarrow a$  where  $\Pr[a = 0] = \Pr[a = 1] = 1/2$ . Since this step is not locally forced, the clever version  $\mathcal{C}(\mathcal{A})$  allows first trying the choice of  $a$  for  $x_j$ , which is not equal to  $x'_j$  with probability  $1/2$ . Therefore,

$$\begin{aligned} \Pr[\rho^{s'} \text{ extendable to } x'] &= \Pr[\rho_{\text{bef}}^{s'} \text{ extendable to } x'] \Pr[a = x'_j | \rho_{\text{bef}}^{s'} \text{ extendable to } x'] \\ &= \Pr[\rho^{s'-1} \text{ extendable to } x'] \cdot 1/2 \\ &= 2^{-s'+1} \cdot 1/2 = 2^{-s'}. \end{aligned}$$

$\square$

### 5.2. Choice of Predicate and Graph

For Lemmas 4.10 and 4.13, we need that the predicate  $P$  be  $h$ -robust for small  $h$ . The following lemma provides two classes of predicates that satisfy this.

LEMMA 5.2. *The predicate  $P = x_1 \oplus \dots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  is  $h$ -robust. A random predicate  $P$  on  $d$  variables is  $\Theta(\log d)$ -robust with probability  $1 - o_d(1)$ .*

PROOF. Predicates of the form  $P = x_1 \oplus \dots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  are  $h$ -robust, since any subset of  $h + 1$  variables includes at least one of the variables  $x_1, \dots, x_{d-h}$ .

Now assume  $P$  is a random  $d$ -ary predicate. Let  $\rho$  be any partial assignment on  $d$  variables which fixes all but  $h + 1$  variables. Let  $E_\rho$  be the event that the predicate  $P$  becomes constant under the partial assignment  $\rho$ . We have  $\Pr[E_\rho] = 2 \cdot 2^{-2^{h+1}} = 2^{1-2^{h+1}}$ .  $P$  is  $h$ -robust if for none of the  $2^{d-h-1} \binom{d}{h+1}$  partial assignments  $\rho$ , the event  $E_\rho$  holds. Taking a union bound,

$$\begin{aligned} \Pr[P \text{ is not } h\text{-robust}] &\leq 2^{d-h-1} \binom{d}{h+1} 2^{1-2^{h+1}} \\ &\leq 2^{d-h-2^{h+1}} d^{h+1} \\ &= o_d(1), \end{aligned}$$

for  $h = \Theta(\log d)$ .  $\square$

In this paper we analyze Goldreich's function  $f_{P,G}$  where  $G \in [n]^{n \times d}$  is a random bipartite graph. For Lemmas 4.10 and 4.13, the graph  $G$  should be a boundary expander, but there is a non-negligible (i.e. inverse polynomial in  $n$ ) probability that  $G$  is not a good boundary expander. However, the following Lemma shows that always except with probability exponentially small in  $n$  the graph is an "imperfect" boundary expander. In the next subsection, we shall see that our results about drunk algorithms when  $G$  is a boundary expander also work when  $G$  is an imperfect boundary expander.

DEFINITION 5.3 (IMPERFECT EXPANSION). *A graph  $G \in [n]^{n \times d}$  is an  $r_{\text{bad}}$ -imperfect  $(r, c)$ -boundary expander if there exists a subset  $I_{\text{bad}} \subseteq R$  of size  $|I_{\text{bad}}| \leq r_{\text{bad}}$  such that  $G \setminus (I_{\text{bad}} \cup \Gamma(I_{\text{bad}}))$ , i.e. the graph obtained by removing vertices  $I_{\text{bad}}$  and  $\Gamma(I_{\text{bad}})$  from  $G$ , is an  $(r, c)$ -boundary expander. We call  $I_{\text{bad}}$  an extraneous set of  $G$ .*

LEMMA 5.4. *A random bipartite graph  $G \in [n]^{n \times d}$  with  $n$  left nodes and  $n$  right nodes, and of right-degree  $d$ , is with probability  $1 - (1/4)^{r_{\text{bad}}}$  an  $r_{\text{bad}}$ -imperfect  $(r, c)$ -boundary expander for any  $c = d - \Omega(d)$ , provided  $r + r_{\text{bad}} \leq r_{\text{max}}(n, d, c)$ , where  $r_{\text{max}} = \Omega(n/d)$ .*

PROOF. Let  $c' = (c + d)/2$ . Let  $I_{\text{bad}}$  be a largest set of right-nodes  $I \subseteq R$  of size at most  $r + r_{\text{bad}}$  such that  $|\Gamma(I)| \leq c'|I|$ . Remove  $I_{\text{bad}}$  and  $\Gamma(I_{\text{bad}})$  from  $G$ . Then any set  $S$  of  $\leq r + r_{\text{bad}} - |I_{\text{bad}}|$  right vertices in  $G \setminus (I_{\text{bad}} \cup \Gamma(I_{\text{bad}}))$  has at least  $c'|S|$  distinct neighbors, and hence has at least  $(2c' - d)|S| = c|S|$  boundary neighbors (because every non-boundary neighbor is connected via  $\geq 2$  edges to  $S$ ). Thus in order to show  $G$  is an  $r_{\text{bad}}$ -imperfect  $(r, c)$ -boundary expander, we just need to show that  $|I_{\text{bad}}| \leq r_{\text{bad}}$ .

We note that the probability that a specific set  $I$  of  $i$  right nodes has  $< c'i$  neighbors is at most

$$\binom{n}{\lfloor c'i \rfloor} \left( \frac{\lfloor c'i \rfloor}{n} \right)^{di} \leq \left( \frac{ne}{\lfloor c'i \rfloor} \right)^{\lfloor c'i \rfloor} \left( \frac{\lfloor c'i \rfloor}{n} \right)^{di}.$$

Thus the probability that  $|I_{\text{bad}}| > r_{\text{bad}}$  is at most

$$\begin{aligned} \sum_{i=r_{\text{bad}}+1}^{r+r_{\text{bad}}} \binom{n}{i} \left(\frac{ne}{\lfloor c'i \rfloor}\right)^{\lfloor c'i \rfloor} \left(\frac{\lfloor c'i \rfloor}{n}\right)^{di} &\leq \sum_{i=r_{\text{bad}}+1}^{r+r_{\text{bad}}} \left(\frac{ne}{i}\right)^i \left(\frac{ne}{c'i}\right)^{c'i} \left(\frac{c'i}{n}\right)^{di} \\ &= \sum_{i=r_{\text{bad}}+1}^{r+r_{\text{bad}}} \left(\left(\frac{i}{n}\right)^{d-c'-1} c^{d-c'} e^{1+c'}\right)^i. \end{aligned}$$

Let  $a_i = \left(\frac{i}{n}\right)^{d-c'-1} c^{d-c'} e^{1+c'}$ . Define

$$r_{\text{max}} = \frac{n}{c} (4c'e^{1+c'})^{-1/(d-c'-1)} = \Omega(n/d).$$

For  $i \leq r_{\text{max}}$ , we have  $a_i \leq 1/4$ . Thus the above sum is at most  $(1/4)^{r_{\text{bad}}}$ .  $\square$

### 5.3. Coping with Imperfect Expansion

LEMMA 5.5. *Let  $f = f_{G,P} : \{0,1\}^n \rightarrow \{0,1\}^m$  be an instance of Goldreich's function. Let  $I \subseteq R$  be a set of right-nodes in  $G$  and define  $\hat{f} = f_{(G \setminus I),P} : \{0,1\}^n \rightarrow \{0,1\}^{m-|I|}$ .*

*Sample  $x' \in \{0,1\}^n$  uniformly at random and let  $b = f(x')$  and  $\hat{b} = \hat{f}(x') = b_{R \setminus I}$ . Let  $\mathcal{A}$  be a drunk backtracking algorithm for inverting  $f$  that returns the exact solution  $x'$  in time  $\leq \text{maxtime}$  with probability  $p$ . Then there exists a drunk backtracking algorithm  $\mathcal{A}'$  for inverting  $\hat{f}(x')$  that given  $b_{R \setminus I}$  with probability at least  $p2^{-|\Gamma(I)|}$  returns the exact solution  $x'$  in time  $\leq \text{maxtime} + |\Gamma(I)|$ .*

A first attempt to prove Lemma 5.5 is to have  $\mathcal{A}'$  convert the output  $\hat{b} \in \{0,1\}^{m-|\Gamma(I)|}$  into a complete output  $b \in \{0,1\}^m$  by guessing the output values  $b_I$  randomly. This guess would be correct with probability  $2^{-|I|}$ , and  $\mathcal{A}'$  could then try to emulate the original algorithm  $\mathcal{A}$  on the complete input  $b$ , by making the same decision that  $\mathcal{A}$  would make at each node of the backtracking tree. The trouble with this approach is that when  $\mathcal{A}$  reaches a node whose partial assignment is inconsistent with a bit in  $b_I$ , it can backtrack.  $\mathcal{A}'$  is only allowed to backtrack from nodes which are inconsistent with bits in  $\hat{b}$ , and so  $\mathcal{A}'$  may be forced to explore backtracking subtrees that  $\mathcal{A}$  is allowed to skip. To fix this problem, we guess the input bits  $x'_{\Gamma(I)}$  instead of guessing the output bits  $b_I$ .

PROOF.  $\mathcal{A}'$  will begin by assigning values to the bits  $x_{\Gamma(I)}$  in a drunk (random) way. With probability  $2^{-|\Gamma(I)|}$ , the resulting partial assignment  $\rho$  agrees with  $x'$ . We are not interested in the behavior of  $\mathcal{A}'$  if the partial assignment  $\rho$  does not agree with  $x'$ . But if it agrees, then we continue  $\mathcal{A}'$  as if  $\mathcal{A}$  were running. However, sometimes  $\mathcal{A}$  tries to assign a value to a variable in  $\Gamma(I)$ : In this case,  $\mathcal{A}'$  has already assigned the correct value to that variable and  $\mathcal{A}'$  does not need to assign a new value. Clearly, since  $\rho$  agrees with  $x'$ ,  $\mathcal{A}$  will never backtrack because of the inconsistency of its current partial assignment with a bit  $b_i$  where  $i \in I$ . Rather,  $\mathcal{A}$  will backtrack because of an inconsistency with a bit  $b_i$  where  $i \in R \setminus I$ ; but, in this case  $\mathcal{A}'$  will also backtrack. To summarize, conditioned on  $\rho$  agreeing with  $x'$ , the running time of  $\mathcal{A}'$  is at most  $|\Gamma(I)|$  steps more than the running time of  $\mathcal{A}$ , and if  $\mathcal{A}$  finds  $x'$  so does  $\mathcal{A}'$ . The statement of the lemma follows.  $\square$

### 5.4. Putting It All Together

PROOF OF THEOREM 2.8. Given predicate  $P$ , we first check that  $P$  satisfies the test that implies the upper bound of Theorem 2.5. Next, we check that  $P$  is  $h$ -robust for

$h = d/2 - \Omega(d)$ . If both checks are satisfied, we say that the predicate has passed the test. By Lemma 5.2, the test satisfies properties (A), (B'), and (C).

Let  $G \in [n]^{n \times d}$  be chosen uniformly at random. By Theorem 2.5 and Markov's inequality,  $f_{P,G}$  has expected preimage size  $\leq M^2$  with probability  $\geq 1 - 1/M$  for  $M = n^{O(1)}2^{2^{-\Theta(d)}n}$ . Also let  $c = d/2 + h$ . Then  $c = d - \Omega(d)$ , and by Lemma 5.4, a random  $G \in [n]^{n \times d}$  is an  $r_{\text{bad}}$ -imperfect  $(r, c)$ -boundary expander with probability  $1 - 2^{-\Theta(n2^{-\Theta(d)})}$  for  $r = \Theta(n/d)$ ,  $r_{\text{bad}} = \Theta(n2^{-\Theta(d)})$ , and  $r + r_{\text{bad}} \leq r_{\text{max}}(n, d, c)$ , with extraneous set  $I_{\text{bad}}$ . To summarize, with probability  $1 - 2^{-n2^{-\Theta(d)} + O(\log n)}$  over the choice of  $G$ , both  $G$  is an  $r_{\text{bad}}$ -imperfect  $(r, c)$ -boundary expander and  $f_{P,G}$  has expected preimage size  $\leq M^2$ . We show that in this case, any drunk backtracking algorithm  $\mathcal{A}$  cannot invert  $\hat{f} = f_{P,G \setminus I_{\text{bad}}}$  with high probability efficiently.

Let  $\mathcal{A}$  be a drunk backtracking algorithm. Choose  $x \in \{0, 1\}^n$  uniformly at random and let  $\hat{b} = f_{P,G \setminus I_{\text{bad}}}(x)$ . By Lemma 4.13, in finding an element in the preimage of  $\hat{b}$  the clever version  $\mathcal{C}(\mathcal{A})$  of  $\mathcal{A}$  makes at least  $\lfloor cr/4 \rfloor = \Omega(n)$  locally unforced assignments on the left-most branch of its backtracking tree. Let  $\rho$  be the partial assignment on the left-most branch after  $\lfloor cr/4 \rfloor$  locally unforced assignments. By Lemma 4.13,  $\rho$  is locally consistent, and by Lemma 5.1, with probability  $1 - 2^{-\Omega(n)}$ , the partial assignment  $\rho$  does not agree with  $x$ . Assume  $\rho$  does not agree with  $x$ . Then

- either  $\rho$  is globally consistent in which case  $\mathcal{C}(\mathcal{A})$  returns  $\mathcal{C}(\mathcal{A})(\hat{b}) \neq x$  from its search of the backtracking tree rooted at  $\rho$ ,
- or  $\rho$  is globally inconsistent, in which case, by Lemma 4.10,  $\mathcal{C}(\mathcal{A})(\hat{b})$  spends  $2^{(c/2-h)r/4-d}$  steps in searching the backtracking tree rooted at  $\rho$ . Noticing that  $c/2 - h = \Omega(d)$ , this amounts to  $2^{\Theta(n)}$  steps.

In either case,  $\mathcal{C}(\mathcal{A})$  and hence  $\mathcal{A}$  does not return  $x$  as output in time better than  $2^{\Theta(n)}$ . So  $\mathcal{A}$  outputs  $x$  in time better than  $2^{\Theta(n)}$  with probability  $\leq p = 2^{-\Theta(n)}$ .

By Lemma 5.5, drunk backtracking algorithms for  $f = f_{P,G}$  itself also cannot return  $x$  given  $b = f(x)$  in time better than  $2^{\Theta(n)}$  with probability better than  $p2^{|\Gamma(I_{\text{bad}})|} = 2^{-\Theta(n)}$ , because  $|\Gamma(I_{\text{bad}})| \leq d|I_{\text{bad}}| = \Theta(n2^{-\Theta(d)})$ .

By Lemma 3.1, drunk backtracking algorithms cannot return any element in the preimage  $f_{P,G}^{-1}(b)$  in time better than  $2^{\Theta(n)}$  with probability better than  $2\sqrt{M^22^{-\Theta(n)}}$ . This probability is at most  $2^{-C(d)n}$  where  $C(d)$  only depends on  $d$  and is positive for large enough  $d$ . This completes the proof.  $\square$

## 6. MYOPIC BACKTRACKING ALGORITHMS

The goal of this section is to prove Theorem 2.11.

### 6.1. Choice of Predicate and Graph

To prove the security of Goldreich's function against drunk backtracking algorithms, we assumed the predicate  $P$  was  $h$ -robust, that the graph  $G$  was an  $(r, c)$ -expander, and that  $G$  and  $P$  were such that  $f_{P,G}$  had small preimages. In the case of myopic backtracking algorithms, we add one more condition on  $P$  and one more condition on  $G$ .

**DEFINITION 6.1** ( $(h, \epsilon)$ -BALANCED PREDICATE). *For a predicate  $P : \{0, 1\}^d \rightarrow \{0, 1\}$ , real number  $\epsilon_{\text{bal}} \in [0, 1/2)$ , and integer  $h \in [0, d - 1]$ , we say predicate  $P$  is  $(h, \epsilon_{\text{bal}})$ -balanced if after fixing all but  $h + 1$  variables,*

$$|\Pr[P(x_1, \dots, x_d) = 0 \mid \text{fixed variables}] - \frac{1}{2}| \leq \epsilon_{\text{bal}}.$$

For example, the predicate  $P_{2,\wedge} = x_1 \oplus \cdots \oplus x_{d-2} \oplus (x_{d-1} \wedge x_d)$  is  $(2,0)$ -balanced and  $(1, \frac{1}{4})$ -balanced. The predicate that sums all its inputs modulo 2 is  $(0,0)$ -balanced. A predicate is  $h$ -robust iff there is some  $\epsilon_{\text{bal}} \in [0, 1)$  such that  $P$  is  $(h, \epsilon_{\text{bal}})$ -balanced.

In other work, a *balanced* predicate is often defined as one where  $|P^{-1}(0)| = |P^{-1}(1)| = 2^{d-1}$ . We would call this a  $(d-1, 0)$ -balanced predicate.

**LEMMA 6.2.** *A random predicate on  $d$  variables is  $(\Theta(\log \frac{d}{\epsilon_{\text{bal}}}), \epsilon_{\text{bal}})$ -balanced with probability  $1 - \exp[-\text{poly}(d/\epsilon_{\text{bal}})]$ . Predicates of the form  $P_{h,Q} = x_1 \oplus \cdots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  are  $(h, 0)$ -balanced.*

**PROOF.** Let  $\rho$  be any partial assignment which fixes all but  $h+1$  variables. There are  $2^{h+1}$  inputs consistent with  $\rho$ : call them  $x_1^\rho, \dots, x_{2^{h+1}}^\rho$ . Let  $E_\rho$  be the event that  $P$  is not balanced under the partial assignment  $\rho$ :  $E_\rho = \{|\#\{i : P(x_i^\rho) = 1\} - 2^h| > 2^{h+1}\epsilon_{\text{bal}}\}$ .

$P$  is balanced if for none of the  $2^{d-h-1} \binom{d}{h+1}$  partial assignments  $\rho$ , the event  $E_\rho$  holds. By a Chernoff bound,  $\Pr[E_\rho] \leq 2e^{-\epsilon_{\text{bal}}^2 2^{h+2}}$ . Taking a union bound,

$$\begin{aligned} \Pr[P \text{ is not } (h, \epsilon_{\text{bal}})\text{-balanced}] &\leq 2^{d-h-1} \binom{d}{h+1} 2e^{-\epsilon_{\text{bal}}^2 2^{h+2}} \\ &\leq 2^{d-h} d^{h+1} e^{-\epsilon_{\text{bal}}^2 2^{h+2}} \\ &= \exp[(h+1) \ln d + (d-h) \ln 2 - \epsilon_{\text{bal}}^2 2^{h+2}]. \end{aligned}$$

Finally, to show the desired result, take  $h = \Theta(\log \frac{d}{\epsilon_{\text{bal}}})$ .

To see that the predicate  $P_{h,Q}(x_1, \dots, x_d) = x_1 \oplus \cdots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  is  $(h, 0)$ -balanced, notice that any subset of  $h+1$  variables includes at least one of the variables  $x_1, \dots, x_{d-h}$ .  $\square$

**LEMMA 6.3.** *A bipartite graph  $G \in [n]^{n \times d}$  chosen uniformly at random from  $[n]^{n \times d}$ , with  $n$  left nodes,  $n$  right nodes, and of right-degree  $d$  has with probability  $\geq 1 - 2^{-n_{\text{bad}}}$  at most  $n_{\text{bad}}$  left nodes of degree  $> d_{\text{left}}$ , provided  $d_{\text{left}} \geq 2ed$  and  $n_{\text{bad}} \geq 2en2^{-d}$ .*

**PROOF.** The probability that there are  $> n_{\text{bad}}$  left vertices of degree  $> d_{\text{left}}$  is at most the probability that there exists a set  $S$  of  $n_{\text{bad}}$  left vertices such that at least  $n_{\text{bad}}d_{\text{left}}$  of the edges of the graph have an endpoint in  $S$ . For each set  $S$  of  $n_{\text{bad}}$  left vertices, this happens with probability at most

$$\binom{nd}{n_{\text{bad}}d_{\text{left}}} \left(\frac{n_{\text{bad}}}{n}\right)^{n_{\text{bad}}d_{\text{left}}} \leq \left(\frac{nde}{n_{\text{bad}}d_{\text{left}}}\right)^{n_{\text{bad}}d_{\text{left}}} \left(\frac{n_{\text{bad}}}{n}\right)^{n_{\text{bad}}d_{\text{left}}} \leq 2^{-dn_{\text{bad}}},$$

where the last inequality is true provided  $d_{\text{left}} \geq 2de$ . Now by a union bound, the probability that such an  $S$  exists is at most

$$\binom{n}{n_{\text{bad}}} 2^{-dn_{\text{bad}}} \leq \left(\frac{ne}{n_{\text{bad}}}\right)^{n_{\text{bad}}} 2^{-dn_{\text{bad}}} \leq 2^{-n_{\text{bad}}}$$

provided  $n_{\text{bad}} \geq 2ne2^{-d}$ .  $\square$

## 6.2. Probability of a Correct Guess

**LEMMA 6.4 (MAIN MYOPIC LEMMA).** *Let  $A$  be an  $(s, r)$ -myopic backtracking algorithm for inverting Goldreich's function  $f_{P,G}$ , where  $s = 2^{-o(d)}n$ . Assume that we are guaranteed that  $A$  makes at least  $s$  assignments on the left-most branch of its backtracking tree before it stops searching that path. Let  $P$  be any  $(h, \epsilon_{\text{bal}})$ -balanced pred-*



icate where  $\epsilon_{\text{bal}} = 2^{-\Omega(d)}$ , and let  $G \in [n]^{m \times d}$  be any  $(r, c)$ -boundary expander with  $m = O(n)$  where all but  $n_{\text{bad}} = 2^{-\Omega(d)}n$  of the left-nodes have degree  $O(d)$ .

Choose  $x' \in \{0, 1\}^n$  uniformly at random and let  $b = f_{P, G}(x')$ . When  $b$  is given as input to  $\mathcal{A}$ , let  $\rho^s(b)$  be the resulting partial assignment on the left-most branch after  $s$  assignments. The probability, over the randomness of  $x' \in \{0, 1\}^n$ , that  $\rho^s(b)$  can be extended to  $x'$  is at most  $2^{-2^{-o(d)}n}$ .

**LEMMA 6.5.** *Assume  $G$  is an  $(r, c)$ -boundary expander of right-degree  $d$ , with at most  $n_{\text{bad}}$  left-nodes of degree bigger than  $d_{\text{left}}$ . Let  $h \geq 0$  be a real number and assume  $c > h + 1$ . Let  $W$  be a set of left-nodes of  $G$ . Then there exists  $U \subseteq W$  such that*

$$|U| \geq \frac{|W| - n_{\text{bad}}}{2d_{\text{left}}d}$$

and for every  $A \subseteq R$  with  $|A| \leq r$ , there is some  $i \in A$  such that  $|\partial_A i \setminus U| > h$ .

**PROOF.** Let  $\hat{c} = \lceil c - h - 1 \rceil$ . Construct  $U$  using the following algorithm:

- $U \leftarrow \emptyset$ .
- For every  $i \in L$ , set  $n_i \leftarrow \begin{cases} \hat{c} & \text{if } i \in W \text{ and } i \text{ has degree at most } d_{\text{left}}; \\ 0 & \text{otherwise.} \end{cases}$
- The following invariant holds every time the following **while** loop checks its loop condition: every right-node connected to a left-node  $j$  has at most  $\hat{c} - n_j$  adjacent left-nodes in  $U$ .
- **while**  $\exists i, n_i > 0$ ,
  - $U \leftarrow U \cup \{i\}$ .
  - $n_i \leftarrow 0$ .
  - For every  $j \in L$  distinct from  $i$ , if  $i$  and  $j$  have a common neighbor, then  $n_j \leftarrow \max\{0, n_j - 1\}$ .

In the beginning,  $\sum_i n_i \geq \hat{c}(|W| - n_{\text{bad}})$ , and in the end,  $\sum_i n_i = 0$ . At each step,  $\sum_i n_i$  decreases by at most  $\hat{c} + d_{\text{left}}(d - 1)$ . Therefore the number of steps we took is

$$|U| \geq \frac{\hat{c}(|W| - n_{\text{bad}})}{\hat{c} + d_{\text{left}}(d - 1)} \geq \frac{|W| - n_{\text{bad}}}{2d_{\text{left}}d}.$$

By the loop invariant, every right-node has at most  $\hat{c}$  adjacent left-nodes in  $U$ . Let  $A \subseteq R$  have size  $|A| \leq r$ . Then by the expansion of  $G$ , there is some  $i \in A$  such that  $|\partial_A i| \geq c$ . It follows that  $|\partial_A i \setminus U| \geq c - \hat{c} > h$ .  $\square$

**PROOF OF LEMMA 6.4.** As the myopic algorithm  $\mathcal{A}$  runs, it may query bits of  $b = f(x')$  in order to decide which assignment to try next. Let  $T(b) \subseteq [m]$  be the set of indices of bits of  $b$  that  $\mathcal{A}$  queries after following the leftmost branch for  $s$  steps. Since  $\mathcal{A}$  is  $(s, r)$ -myopic, we know  $|T(b)| \leq r$ . The decisions of  $\mathcal{A}$  are based only on the bits in  $T(b)$ , so whenever  $b'_{T(b)} = b_{T(b)}$ , it must be that  $\rho^s(b') = \rho^s(b)$  and  $T(b') = T(b)$ .

For any  $\hat{b} \in \{0, 1\}^n$ , define the set

$$E_{\hat{b}} = \{x' \in \{0, 1\}^n : f(x')_{T(\hat{b})} = \hat{b}_{T(\hat{b})}\}.$$

We begin by showing that the sets  $\{E_{\hat{b}} : \hat{b} \in \{0, 1\}^n\}$  form a partition of  $\{0, 1\}^n$ . These sets cover all of  $\{0, 1\}^n$  because  $x' \in E_{f(x')}$  for every  $x' \in \{0, 1\}^n$ . Now assume, for  $\hat{b}, \hat{b}' \in \{0, 1\}^n$ , the sets  $E_{\hat{b}}$  and  $E_{\hat{b}'}$  share a string  $x'$ . Then  $f(x')_{T(\hat{b})} = \hat{b}_{T(\hat{b})}$ , so  $T(f(x')) = T(\hat{b})$  and similarly  $T(f(x')) = T(\hat{b}')$ . Thus,  $T(\hat{b}) = T(\hat{b}')$ , and  $\hat{b}_{T(\hat{b})} = f(x')_{T(\hat{b})} = \hat{b}'_{T(\hat{b}'})$ . This means that any two intersecting sets  $E_{\hat{b}}$  and  $E_{\hat{b}'}$  are equal.

Since the sets  $E_{\hat{b}}$  partition  $\{0,1\}^n$ , we can prove the Lemma by showing that for every  $\hat{b}$ , the probability that  $\rho^s$  can be extended to  $x'$ , conditioned on event  $x' \in E_{\hat{b}}$ , is at most  $2^{-2^{-o(d)}n}$ .

Therefore from now on we fix  $\hat{b}$ . Conditioning on the event  $x' \in E_{\hat{b}}$  fixes  $\rho^s$ . By Lemma 6.5 with  $W = \text{Vars}(\rho^s)$ , there exists a set of input nodes  $U \subseteq \text{Vars}(\rho^s)$  of size  $(s - n_{\text{bad}})/(2d\Theta(d)) = 2^{-o(d)}n$  such that every subset of  $T(\hat{b})$  has boundary expansion  $> h$  outside  $U$ . We know that

$$\Pr[\rho^s \text{ can be extended to } x' | x' \in E_{\hat{b}}] \leq \Pr[x'_U = \rho^s_U | x' \in E_{\hat{b}}],$$

so it suffices to show

$$\Pr[x_U = y | x' \in E_{\hat{b}}] = 2^{-2^{-o(d)}n}, \quad (6)$$

for  $y = \rho^s_U$ .

Here is a two-sentence overview of the proof of (6) for any  $y \in \{0,1\}^{|U|}$ . We first show that  $x_U$  has little influence on the distribution of  $b_{T(\hat{b})}$ . Then by Bayes' rule, we conclude that the bits  $b_{T(\hat{b})}$  do not contain much information about  $x'_U$ .

Order the nodes in  $T(\hat{b})$  as  $v_1, v_2, \dots, v_{|T(\hat{b})|}$  such that for every  $1 \leq i \leq |T(\hat{b})|$ , we have  $|\Gamma(T_i) \setminus (\Gamma(T_{i-1}) \cup U)| \geq h + 1$  for  $T_i = \{v_1, \dots, v_i\}$ . This ordering is possible because every subset of  $T(\hat{b})$  has a node with boundary  $> h$  outside  $U$ . For any  $y \in \{0,1\}^{|U|}$ , we have

$$\begin{aligned} \Pr[x' \in E_{\hat{b}} | x_U = y] &= \prod_{i=1}^{|T(\hat{b})|} \Pr[b_{v_i} = \hat{b}_{v_i} | b_{T_{i-1}} = \hat{b}_{T_{i-1}}, x_U = y] \\ &\in [(\frac{1}{2} - \epsilon_{\text{bal}})^{|T(\hat{b})|}, (\frac{1}{2} + \epsilon_{\text{bal}})^{|T(\hat{b})|}], \end{aligned}$$

since  $P$  is  $(h, \epsilon_{\text{bal}})$ -balanced and since for every  $1 \leq i \leq |T(\hat{b})|$ ,  $v_i$  has at least  $h + 1$  neighbors outside  $\Gamma(T_{i-1})$  and  $U$ . Using Bayes' rule, for any  $y, y' \in \{0,1\}^{|U|}$ ,

$$\begin{aligned} \frac{\Pr[x'_U = y' | x' \in E_{\hat{b}}]}{\Pr[x'_U = y | x' \in E_{\hat{b}}]} &= \frac{\Pr[x' \in E_{\hat{b}} | x'_U = y'] \Pr[x'_U = y']}{\Pr[x' \in E_{\hat{b}} | x'_U = y] \Pr[x'_U = y]} \\ &= \frac{\Pr[x' \in E_{\hat{b}} | x'_U = y']}{\Pr[x' \in E_{\hat{b}} | x'_U = y]} \\ &\geq \left( \frac{1 - 2\epsilon_{\text{bal}}}{1 + 2\epsilon_{\text{bal}}} \right)^{|T(\hat{b})|}. \end{aligned}$$

Fixing  $y$  and summing the above inequality over all  $y' \in \{0,1\}^{|U|}$ , we get

$$\frac{1}{\Pr[x'_U = y | x' \in E_{\hat{b}}]} \geq 2^{|U|} \left( \frac{1 - 2\epsilon_{\text{bal}}}{1 + 2\epsilon_{\text{bal}}} \right)^{|T(\hat{b})|}.$$

Since  $|U| = 2^{-o(d)}n$ ,  $\epsilon_{\text{bal}} = 2^{-\Omega(d)}$  and  $|T(\hat{b})| \leq m = O(n)$ , Equation (6) follows.  $\square$

### 6.3. Clever Myopic Algorithms

We will need a stronger version of Lemma 4.15.

**LEMMA 6.6.** *Let  $J \subseteq L$  have size  $|J| \leq cr/4$ . Then there exists a closure  $C$  for  $J$  such that  $|C| \leq 2c^{-1}|J|$  and  $|\partial C \setminus J| \leq c|C|/2$ .*

*Furthermore, if  $C'$  is any set such that  $|C'| \leq 2c^{-1}|J|$  and  $|\partial C' \setminus J| \leq c|C'|/2$ , then we can pick  $C$  to be a superset of  $C'$ .*

PROOF. The proof is the same as the proof of Lemma 4.15, except for the following change. Instead of saying “Let  $C$  be a largest nonexpanding set with  $\leq r/2$  vertices”, the proof should say “Let  $C$  be a largest superset of  $C'$  which is nonexpanding and has  $\leq r/2$  vertices.” We know there is such a set because  $C'$  itself is a superset of  $C'$  which is nonexpanding and has  $\leq r/2$  vertices.  $\square$

Consider a myopic backtracking algorithm  $\mathcal{A}$  and the clever version  $\mathcal{C}(\mathcal{A})$ . In order to decide which assignment to make next,  $\mathcal{C}(\mathcal{A})$  queries the same bits of  $b$  that  $\mathcal{A}$  would, but it also checks at every step whether the partial assignment is locally consistent. Since  $\mathcal{C}(\mathcal{A})$  makes this additional kind of query, it is not clear whether  $\mathcal{C}(\mathcal{A})$  is myopic. However, as the following lemma shows, it is possible to create a myopic algorithm which behaves in the same way as  $\mathcal{C}(\mathcal{A})$  by reading a limited number of additional bits of  $b$ .

LEMMA 6.7. *Let  $\mathcal{A}$  be an  $(s, t)$ -myopic backtracking algorithm for inverting Goldreich’s function  $f_{P,G}$ . If  $G$  is an  $(r, c)$ -boundary expander,  $s \leq cr/4$  and  $P$  is a  $(c/2 - 1)$ -robust predicate, then there is an  $(s, t + 2c^{-1}s)$ -myopic backtracking algorithm  $\mathcal{A}'$  which has the same backtracking tree as  $\mathcal{C}(\mathcal{A})$ .*

PROOF. During the task of finding  $x \in f_{P,G}^{-1}(b)$ , algorithm  $\mathcal{A}'$  will maintain a set  $C \subseteq R$  of right-nodes of  $G$ . Whenever  $\mathcal{A}'$  adds a new node  $i$  to  $C$ , it will also query the corresponding bit  $b_i$ . When  $\mathcal{A}'$  finishes exploring a subtree and consequently forgets some bits of  $b$ , it removes the corresponding nodes from the set  $C$ : so  $\mathcal{A}'$  always knows every bit  $b_i$  for  $i \in C$ . The algorithm will use this knowledge of  $b$  in order to emulate the clever decisions made by  $\mathcal{C}(\mathcal{A})$ .

$\mathcal{A}'$  will maintain the following invariant at every point in its execution where it has assigned values to less than  $s$  variables. Let  $\rho$  be the current partial assignment, let  $x_j \leftarrow a$  be the next assignment that  $\mathcal{A}$  would make at this point, and let  $J = \text{Vars}(\rho) \cup \{j\}$ . Then  $C$  is a closure for  $J$ ,  $|C| \leq 2c^{-1}|J|$ , and  $|\partial C \setminus J| \leq c|C|/2$ . Since  $s \leq cr/4$ , Lemma 6.6 ensures that  $\mathcal{A}'$  can maintain this invariant.

Now, whenever  $\mathcal{C}(\mathcal{A})$  makes a new assignment, it makes the same assignment  $x_j \leftarrow a$  that  $\mathcal{A}$  would make, unless  $x_j \leftarrow 1 - a$  is locally forced. Therefore, to see that  $\mathcal{A}'$  can emulate  $\mathcal{C}(\mathcal{A})$ , all that remains is to show that the bits  $b_i$  for  $i \in C$  always provide enough information to determine whether any partial assignment to the variables in  $J$  is locally consistent. Indeed, if a partial assignment to  $J$  is consistent with  $C$ , then it is locally consistent by definition, and conversely, if it is locally consistent, then by Lemma 4.16 it is consistent with  $C$ .  $\square$

#### 6.4. Coping with Imperfect Expansion

So far, when studying the behavior of myopic backtracking algorithms, we have assumed that the graph used to construct Goldreich’s function is an  $(r, c)$ -boundary expander. However, as discussed in Section 5.2, the probability that a graph is not a boundary expander is non-negligible. Here we show that the results in this section also apply to imperfect boundary expanders, analogously to Lemma 5.5.

LEMMA 6.8. *Let  $f = f_{G,P} : \{0, 1\}^n \rightarrow \{0, 1\}^m$  be an instance of Goldreich’s function. Let  $I \subseteq R$  be a set of right-nodes in  $G$  and define  $\hat{f} = f_{(G \setminus I), P} : \{0, 1\}^n \rightarrow \{0, 1\}^{m - |I|}$ .*

*Sample  $x' \in \{0, 1\}^n$  uniformly at random and let  $b = f(x)$  and  $\hat{b} = \hat{f}(x) = b_{R \setminus I}$ . Let  $\mathcal{A}$  be an  $(s, t)$ -myopic backtracking algorithm for inverting  $f$  that returns the exact solution  $x'$  in time  $\leq \text{maxtime}$  with probability  $p$ . Then there exists an  $(s, t)$ -myopic backtracking algorithm  $\mathcal{A}'$  for inverting  $\hat{f}(x')$  that given  $b_{R \setminus I}$  with probability at least  $p2^{-|\Gamma(I)|}$  returns the exact solution  $x'$  in time  $\leq \text{maxtime} + |\Gamma(I)|$ .*

PROOF. The proof of Lemma 5.5 gives us a randomized backtracking algorithm  $\mathcal{A}'$  which with probability  $\geq p2^{-|\Gamma(I)|}$  returns  $x'$  in time  $\leq \text{maxtime} + |\Gamma(I)|$ . This algorithm is  $(s, t)$ -myopic, since while it is guessing the bits  $x_{\Gamma(I)}$  it does not look at  $b$  at all, and the rest of its decisions are made according to the myopic algorithm  $\mathcal{A}$ .  $\square$

### 6.5. Putting It All Together

PROOF OF THEOREM 2.11. The proof is the same as the proof of Theorem 2.8 in Section 5.4, with the following changes.

- We test the predicate  $P$  with the same test as in Theorem 2.8, but we additionally test that  $P$  is  $(h, \epsilon_{\text{bal}})$ -balanced for  $h = d/2 - \Omega(d)$  and  $\epsilon_{\text{bal}} = 2^{-\Omega(d)}$ . If both the old and new tests are satisfied, we say that  $P$  has passed the test. By Lemma 6.2, this new test satisfies properties (A), (B'), and (C).
- We use Lemma 6.3 to show that a random  $G$  has with probability  $1 - 2^{-2^{-\Theta(d)}n}$  no more than  $n_{\text{bad}} = 2en2^{-d}$  left vertices of degree  $> 2ed$ .
- Rather than assuming  $\mathcal{A}$  is a drunk algorithm, we assume  $\mathcal{A}$  is  $(s, t)$ -myopic, where  $s = 2^{-o(d)}n$  and  $t = r/2 = \Omega(n/d)$ . Let  $s' = \min\{s, \lfloor cr/4 \rfloor\} = 2^{-o(d)}n$ . Then  $\mathcal{A}$  is  $(s', t)$ -myopic. By Lemma 6.7, the clever version  $\mathcal{C}(\mathcal{A})$  is  $(s', t + r/2)$ -myopic, so we can apply Lemma 6.4 to  $\mathcal{C}(\mathcal{A})$ . As for the success probability of algorithm  $\mathcal{A}$  on  $f_{P, G \setminus I_{\text{bad}}}$  in finding  $x$  itself, instead of the upper bound of  $p = 2^{-\Theta(n)}$ , we get the upper bound of  $p = 2^{-2^{-o(d)}n}$ .
- We use Lemma 6.8 where the proof of Theorem 2.11 uses Lemma 5.5. This shows a drunk backtracking algorithm on  $f_{P, G}$  has success probability of at most  $2^{-2^{-o(d)}n}$  in finding  $x$  itself. This shows that the success probability of finding any element in the preimage is at most  $2\sqrt{M^2 2^{-2^{-o(d)}n}}$ , and this completes the proof.

$\square$

## 7. MYOPIC AND DRUNK DPLL BACKTRACKING ALGORITHMS

Here we prove Theorem 2.14.

### 7.1. Simulating DPLL Algorithms

Let us forget myopic and drunk algorithms for a moment, and compare backtracking algorithms as described by Definition 2.6 to DPLL backtracking algorithms described by Definition 2.13. Both kinds of algorithm have the option at every step of taking a free variable  $x_j$  and a bit  $a$  and trying first the assignment  $x_j \leftarrow a$  and then, if no solution was found on that branch, the assignment  $x_j \leftarrow 1 - a$ . A DPLL algorithm is also able to make a DPLL assignment  $x_j \leftarrow a$  and skip the alternative assignment  $x_j \leftarrow 1 - a$ . The following lemma shows that this additional ability does not help a DPLL algorithm, except to decrease the number of nodes it must explore by a factor of at most  $2^d$ .

LEMMA 7.1. *Let  $f_{P, G}$  be an instance of Goldreich's function, where  $P$  is any  $d$ -ary predicate and  $G$  is any graph. For any DPLL backtracking algorithm  $\mathcal{D}$ , there is a (non-DPLL) backtracking algorithm  $S(\mathcal{D})$  which simulates  $\mathcal{D}$ : When algorithms  $\mathcal{D}$  and  $S(\mathcal{D})$  are given  $b$  and asked to find some  $x \in f_{P, G}^{-1}(b)$ , then they both return the same result, and the backtracking tree of  $S(\mathcal{D})$  contains at most  $2^d$  times as many nodes as that of  $\mathcal{D}$ .*

PROOF. Whenever  $\mathcal{D}$  makes a non-DPLL assignment  $x_j \leftarrow a$ , the simulation  $S(\mathcal{D})$  makes the same assignment. However, if  $\mathcal{D}$  makes a DPLL assignment  $x_j \leftarrow a$ , then the behavior of  $S(\mathcal{D})$  depends on whether the assignment is a unit clause or a pure literal.

If  $x_j \leftarrow a$  is a pure literal,  $\mathcal{S}(\mathcal{D})$  postpones making this assignment by adding it to a “to-do list” of pure literal assignments. The following invariant is always maintained:

*If the union of the current partial assignment of  $\mathcal{S}(\mathcal{D})$  together with its to-do list contradicts any equation  $b_i = f_{P,G}(x)_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$ , then the current partial assignment without the to-do list contradicts that same equation.*

This means that whenever  $\mathcal{D}$  returns back from a recursion because some bit  $b_i$  has been contradicted,  $\mathcal{S}(\mathcal{D})$  can also return back in  $\leq 2^d - 1$  steps by exhaustively assigning values to all of the variables  $x_{G_{i,1}}, \dots, x_{G_{i,d}}$  which are still free. (Assuming  $P$  is non-trivial, it has at most  $d - 1$  free variables at this point, and  $2^d - 1$  is the number of nodes in a complete binary tree of depth  $d - 1$ .)

The other possible action  $\mathcal{D}$  might take is to assign a unit clause  $x_j \leftarrow a$ . This means that there is some output bit  $i$  such that the equation  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$  implies  $x_j = a$ . In this case,  $\mathcal{S}(\mathcal{D})$  first makes the assignment  $x_j \leftarrow 1 - a$ . Together with the assignments in the to-do list, this contradicts the equation  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$ , so by the invariant,  $\mathcal{S}(\mathcal{D})$  can exhaust the branch in  $\leq 2^d - 1$  steps.  $\mathcal{S}(\mathcal{D})$  is then free to make the DPLL assignment  $x_j \leftarrow a$ .

If  $\mathcal{D}$  succeeds in finding a complete input  $x \in f^{-1}(b)$ , then  $\mathcal{S}(\mathcal{D})$  proceeds to make all the pure literal assignments in its to-do list, and arrives at the same complete assignment  $x$ .  $\square$

## 7.2. Drunk DPLL Algorithms

LEMMA 7.2. *If  $\mathcal{D}$  is a drunk DPLL backtracking algorithm, then there is a non-DPLL backtracking algorithm  $\mathcal{S}'(\mathcal{D})$  that relates to  $\mathcal{D}$  in the same way as  $\mathcal{S}(\mathcal{D})$  in Lemma 7.1, except that  $\mathcal{S}'(\mathcal{D})$  is drunk, and also might return a different  $x \in f^{-1}(b)$  from the one  $\mathcal{S}(\mathcal{D})$  returns.*

PROOF. The simulation  $\mathcal{S}(\mathcal{D})$  from the proof of Lemma 7.1 makes four kinds of assignment. The first kind copies the non-DPLL assignments made by  $\mathcal{D}$ . These are already drunk, so  $\mathcal{S}'(\mathcal{D})$  can behave the same way. The second kind of assignment is made when  $\mathcal{S}(\mathcal{D})$  is exhaustively assigning values some set of  $\leq d - 1$  variables. In this case, we lose nothing by having  $\mathcal{S}'(\mathcal{D})$  behave the same way except to try each pair of assignments  $x_j \leftarrow 0$  and  $x_j \leftarrow 1$  in a random order. The third kind of assignment is when  $\mathcal{D}$  has assigned a unit clause  $x_j \leftarrow a$ . In this case,  $\mathcal{S}(\mathcal{D})$  first tries the incorrect assignment  $x_j \leftarrow 1 - a$ , but we lose nothing by having  $\mathcal{S}'(\mathcal{D})$  try the assignments  $x_j \leftarrow a$  and  $x_j \leftarrow 1 - a$  in random order.

The fourth and final kind of assignment  $\mathcal{S}(\mathcal{D})$  makes is when  $\mathcal{D}$  has found a solution  $x \in f^{-1}(b)$ , and  $\mathcal{S}(\mathcal{D})$  proceeds to make all the assignments in its to-do list of pure literal assignments, in the same order they were added to the list. In this case,  $\mathcal{S}'(\mathcal{D})$  will make the assignments in *reverse* order, and will chose the bit to assign randomly in each case. If  $x_j \leftarrow a$  is a pure literal with respect to a partial assignment  $\rho$ , then it is still a pure literal with respect to any  $\rho'$  which extends  $\rho$ . Therefore, if  $\mathcal{S}'(\mathcal{D})$  makes assignments in its to-do list in reverse order, then at each step, the remaining assignments still form a sequence of pure literal assignments. Now, if the last assignment on the to-do list is  $x_j \leftarrow a$  and  $\mathcal{S}'(\mathcal{D})$  drunkenly assigns  $x_j \leftarrow 1 - a$  instead, let  $x'$  be the full assignment we get by applying the remaining pure literals from the to-do list. Now, either  $f(x') = b$ , in which case we continue making assignments in the to-do list in reverse order, or for some  $i$ ,  $f(x')_i \neq b_i$ , and since the remaining assignments are all pure literals, there is no way to satisfy  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$  given the values already

assigned. In the latter case, we exhaust all possible assignments to those variables in  $\leq 2^d - 1$  steps, and continue with the correct assignment  $x_j \leftarrow a$ .  $\square$

PROOF OF THEOREM 2.14 FOR DPLL DRUNK BACKTRACKING ALGORITHMS. The theorem in the case of DPLL drunk backtracking algorithms follows immediately from Theorem 2.8 and Lemma 7.2.  $\square$

### 7.3. Myopic DPLL Algorithms

DEFINITION 7.3 (NONMONOTONE PREDICATE). *Let  $0 \leq h < d$  be an integer. The predicate  $P : \{0, 1\}^d \rightarrow \{0, 1\}$  is  $h$ -nonmonotone iff after any partial assignment of values to the input variables of  $P$  that lets  $> h$  of the input variables be free, the resulting restricted predicate is not constant and has the following additional property. Pick any input bit  $x_i$  among the  $\geq h + 1$  unrestricted inputs. Then either the restricted predicate does not depend on  $x_i$ , or the restricted predicate is not monotone in  $x_i$ .*

LEMMA 7.4. *The predicate  $P = x_1 \oplus \cdots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  is  $(h + 1)$ -nonmonotone. A random predicate  $P$  on  $d$  variables is  $\Theta(\log d)$ -nonmonotone with probability  $1 - o_d(d)$ .*

PROOF. By Lemma 5.2, we may assume that  $P$  is  $h$ -robust, and so only the “additional property” part of Definition 7.3 remains to be shown.

If we fix all but  $h + 1$  input bits and select an input bit  $x_i$  among those  $h + 1$ , then the probability that a random  $d$ -ary predicate is monotone nondecreasing in  $x_i$  is exactly  $(3/4)^{2^h}$ . Taking a union bound, the probability that for any choice of  $h + 1$  variables, together with an index  $i$  among those  $h + 1$  and a way of fixing the remaining  $d - h - 1$  variables, the predicate becomes monotone in  $x_i$  is at most

$$2 \binom{d}{h+1} 2^{d-h-1} (h+1) (3/4)^{2^h},$$

which is  $\exp(-\text{poly}(d))$  if we take  $h = \Theta(\log d)$ .

Now, consider a predicate  $P_{h,Q} = x_1 \oplus \cdots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  where  $Q$  is any  $h$ -ary predicate. Consider any subset  $S \subseteq [d]$  of  $h + 2$  variable indices, together with an index  $i \in S$  and a partial assignment  $\rho$  that fixes  $x_{[d] \setminus S}$ . We are to show that after the assignments in  $\rho$  are fixed,  $P$  either does not depend on  $x_i$  or is not monotone in  $x_i$ . We have two cases.

*Case 1.*  $1 \leq i \leq d - h$ . Then  $x_i$  is not one of the inputs to the predicate  $Q$ . Since  $|S| \geq h + 2$ , there is at least one other unrestricted input  $x_j$  that is not an input to  $Q$ , so our predicate has the form  $x_i \oplus x_j \oplus P'(x_{[d] \setminus \{i,j\}})$ . This is not monotone in  $x_i$ .

*Case 2.*  $d - h + 1 \leq i \leq d$ . In this case,  $x_i$  is an input to  $Q$ . Since  $|S| \geq h + 1$ , there is at least one unrestricted input  $x_j$  that is not an input to  $Q$ , so our predicate has the form  $x_j \oplus P'(x_i, x_{[d] \setminus \{i,j\}})$  where  $P'$  is a  $(d - 1)$ -ary predicate. We may assume that after assignments in  $\rho$  are fixed,  $P'$  does not ignore  $x_i$ , so there is some value  $\hat{x}$  for  $x_{[d] \setminus \{i,j\}}$  which is consistent with  $\rho$  and such that  $P'(0, \hat{x}) \neq P'(1, \hat{x})$ . For different values of  $x_j$ , then,  $P$  increases or decreases with  $x_i$ , so  $P$  is not monotone in  $x_i$ .  $\square$

LEMMA 7.5. *Let  $f_{G,P}$  be an instance of Goldreich’s function for graph  $G$  and an  $h$ -nonmonotone predicate  $P$ . Consider the execution of a DPLL backtracking algorithm which is searching for  $x \in f^{-1}(b)$ , where the current partial assignment is  $\rho$ . Let  $I \subseteq R$  be a set of indices such that every node in  $R \setminus I$  has at least  $h + 1$  distinct neighbors which are not in  $\text{Vars}(\rho)$ . Then without reading any bits  $b_i$  for  $i \notin I$ , it is possible to know all the DPLL assignments which can be made starting from  $\rho$ .*

PROOF. In order to know which unit clause assignments can be made, iterate through the bits  $b_i$  for  $i \in I$ . In each case, check whether, given  $\rho$ , the equation  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$  together with  $\rho$  implies any variable  $x_j$  has a particular value  $a$ . If any of these equations force  $x_j$  to take a value  $a$ , then  $x_j \leftarrow a$  is a unit clause.

Finding all the pure literal assignments requires a bit more work. For every possible assignment  $x_j \leftarrow a$ , check whether it is a pure literal assignment as follows. First, iterate through all output bits  $b_i$  – even the ones we are not allowed to read – and in each case, consider the equation  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$ . Even if we don't know  $b_i$ , we can still check whether, after fixing the variables in  $\rho$ , the truth of the equation can ever depend on the value of  $x_j$  (equivalently, whether  $P$  ignores the input  $x_j$  once  $\rho$  is fixed). If the truth never depends on  $x_j$ , we call output  $b_i$  *passive* with respect to  $x_j$ . Now, iterate through the bits  $b_i$  for  $i \in I$ , and note which of the equations  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$  can never be changed to false by setting  $x_j = a$ . Call these output bits *monotone toward*  $x_j = a$ . If  $x_j$  is only connected to outputs which are passive with respect to  $x_j$  and outputs  $i \in I$  which are monotone toward  $x_j = a$ , then  $x_j \leftarrow a$  is a pure literal assignment.

What is left is to show that the above procedure finds every unit clause and pure literal assignment.

If  $x_j \leftarrow a$  is a unit clause assignment, then there must be some output bit  $b_i$  such that the equation  $b_i = P(x_{G_{i,1}}, \dots, x_{G_{i,d}})$  implies  $x_j = a$ . Since  $P$  is  $h$ -nonmonotone, this implies that output  $i$  must be connected to  $\leq h$  inputs not in  $\text{Vars}(\rho)$ , so  $i \in I$ , and so the above procedure finds the assignment.

If  $x_j \leftarrow a$  is a pure literal, then given  $\rho$ , every output bit  $b_i$  connected to  $x_j$  is either passive with respect to  $x_j$  or is monotone toward  $x_j = a$ . Now, if an output bit  $b_i$  is not passive with respect to  $x_j$  but is monotone toward  $x_j = a$ , then since  $P$  is  $h$ -nonmonotone,  $b_i$  must be connected to  $\leq h$  inputs which are not in  $\text{Vars}(\rho)$ . Therefore, the above procedure will find  $x_j \leftarrow a$ .  $\square$

#### PROOF OF THEOREM 2.14 FOR DPLL MYOPIC BACKTRACKING ALGORITHMS.

Given a predicate  $P$ , we first check that  $P$  satisfies the test of Theorem 2.11. We then check that  $P$  is  $h$ -nonmonotone, for  $h = d/2 - \Omega(d)$ . If both checks are satisfied, we say that the predicate has passed the test. By Lemma 7.4, the test satisfies properties (A), (B'), and (C).

Let  $t_{\text{non-DPLL}}$  be the value given by Theorem 2.11 such that Goldreich's function is secure against  $(s, t_{\text{non-DPLL}})$ -myopic backtracking algorithms. The proof of Theorem 2.11 guarantees that we can have  $t_{\text{non-DPLL}} = \Omega(n/d)$ .

Let  $G \in [n]^{n \times d}$  be chosen uniformly at random. Let  $c = d/2 + h$ . Then  $c = d - \Omega(d)$ , and by Lemma 5.4,  $G$  is an  $r_{\text{bad}}$ -imperfect  $(r, c)$ -boundary expander with probability  $\geq 1 - 2^{-\Theta(n/d)}$  for  $r = \Omega(n/d)$ ,  $r \leq t_{\text{non-DPLL}}$ ,  $r_{\text{bad}} = r/3$ , and  $r + r_{\text{bad}} \leq r_{\text{max}}(n, d, c)$ , with extraneous set  $I_{\text{bad}}$ .

Given  $s$  such that  $s/n = 2^{-o(d)}$ , let  $\mathcal{D}$  be an  $(s, t)$ -myopic DPLL backtracking algorithm, where  $t = r/3 = \Omega(n/d)$ . Let  $s' = \min\{s, \lfloor cr/6 \rfloor\} = 2^{-o(d)}n$ . Then  $\mathcal{D}$  is an  $(s', t)$ -myopic DPLL algorithm. By Lemma 7.1, there is a non-DPLL algorithm  $\mathcal{S}(\mathcal{D})$  which produces the same result as  $\mathcal{D}$  and takes at most  $2^d$  as long. We will show that  $\mathcal{S}(\mathcal{D})$  can be turned into a myopic algorithm too: that is, we will design an  $(s, t_{\text{non-DPLL}})$ -myopic backtracking algorithm  $\mathcal{S}'(\mathcal{D})$  which has the same backtracking tree as  $\mathcal{S}(\mathcal{D})$ . Theorem 2.11 tells us that Goldreich's function is secure against  $(s, t_{\text{non-DPLL}})$ -myopic non-DPLL backtracking algorithms. Thus, Goldreich's function is secure against  $\mathcal{S}'(\mathcal{D})$  and hence also against  $\mathcal{D}$ .

When finding a preimage  $x \in f^{-1}(b)$  to Goldreich's function, the myopic DPLL algorithm  $\mathcal{D}$ , and therefore its simulation  $\mathcal{S}(\mathcal{D})$ , uses two sources of information. In order to behave in the same way as  $\mathcal{S}(\mathcal{D})$ , the myopic algorithm  $\mathcal{S}'(\mathcal{D})$  must obtain both kinds

of information. First,  $S(\mathcal{D})$  reads bits of  $b$ , but it reads no more than  $t = r/3$  bits before it has assigned values to  $s'$  variables. In order to have this information,  $S'(\mathcal{D})$  reads the same bits of  $b$  that  $\mathcal{D}$  does. Second,  $S(\mathcal{D})$  knows at all times the set of all DPLL assignments that can be made. To obtain this knowledge,  $S'(\mathcal{D})$  will maintain a set  $C \subseteq R$  of right-nodes of  $G$ , and  $S'(\mathcal{D})$  will make sure it has always read all the bits in  $C$  by reading  $b_i$  whenever it adds a node  $i$  to  $C$ . (The set  $C$  plays the same role here as in the proof of Lemma 6.7.)  $C$  will always contain every node in the extraneous set  $I_{\text{bad}}$ . In addition,  $S'(\mathcal{D})$  will maintain the following invariants:

- $C \setminus I_{\text{bad}}$  is a closure for  $\text{Vars}(\rho) \setminus \Gamma(I_{\text{bad}})$  in the graph  $\hat{G} = G \setminus (I_{\text{bad}} \cup \Gamma(I_{\text{bad}}))$ .
- $|C \setminus I_{\text{bad}}| \leq 2c^{-1}|\text{Vars}(\rho)|$ .
- $|\partial C \setminus (\text{Vars}(\rho) \cup \Gamma(I_{\text{bad}}))| \leq c|C \setminus I_{\text{bad}}|/2$ .

By Lemma 6.6, applied to the graph  $\hat{G}$  instead of the imperfectly expanding  $G$ , algorithm  $S'(\mathcal{D})$  can maintain these properties as long as it has assigned less than  $s' \leq \lfloor cr/4 \rfloor$  variables. By Lemma 7.5, reading the bits in the set  $C$  is enough for  $S'(\mathcal{D})$  to know all the DPLL assignments that can be made, and so  $S'(\mathcal{D})$  has enough knowledge to behave in the same way as  $S(\mathcal{D})$ . Before assigning values to  $s'$  variables,  $S'(\mathcal{D})$  reads at most  $r/3$  bits of  $b_i$  because  $\mathcal{D}$  read them, at most  $r_{\text{bad}} = r/3$  bits from  $I_{\text{bad}}$ , and at most  $2c^{-1}s' = r/3$  bits from  $C \setminus I_{\text{bad}}$ , so  $S'(\mathcal{D})$  is  $(s', r)$ -myopic, and therefore  $(s', t_{\text{non-DPLL}})$ -myopic.  $\square$

## 8. MINISAT EXPERIMENT

Inverting Goldreich’s function can be seen as the task of solving a constraint satisfaction problem with a planted solution. This suggests the use of a general-purpose SAT solver to solve the constraint satisfaction problem. We performed an experiment using MiniSat version 2.0 beta [Eén and Sörensson 2003; Eén and Biere 2005], which is one of the best publicly available SAT solvers. We always use the degree-five predicate  $P_5(x) = x_1 \oplus x_2 \oplus x_3 \oplus (x_4 \wedge x_5)$ . For each trial, we choose a new random graph of right-degree 5. MiniSat requires a boolean formula in conjunctive normal form as input, so we represent each constraint  $P(x_{j_1}, x_{j_2}, x_{j_3}, x_{j_4}, x_{j_5}) = v_i$  by 16 clauses: one for each truth assignment to  $x_{j_1}, \dots, x_{j_5}$  that would violate the constraint.

We ran MiniSat on a Lenovo T61 laptop with 2GB of RAM and a 2.00GHz Intel T7300 Core Duo CPU. Fig. 1 plots the number of seconds taken to find a solution versus the input size  $n$ . The graph is plotted on a logarithmic scale. The time appears to grow exponentially in  $n$ .

## 9. ACKNOWLEDGMENTS

The authors benefited from helpful discussions with Alekh Agarwal and Amir Shpilka.

## REFERENCES

- Michael Alekhnovich, Edward A. Hirsch, and Dmitry Itsykson. 2005. Exponential Lower Bounds for the Running Time of DPLL Algorithms on Satisfiable Formulas. *Journal of Automated Reasoning* 35 (2005), 51–72.
- Benny Applebaum. 2013. Pseudorandom Generators with Long Stretch and Low Locality from Random Local One-Way Functions. *SIAM J. Comput.* 42, 5 (2013), 2008–2037.
- Benny Applebaum, Boaz Barak, and Avi Wigderson. 2010. Public-key cryptography from different assumptions. In *Proceedings of the 42nd ACM Symposium on Theory of Computing, STOC 2010, Cambridge, Massachusetts, USA, 5-8 June 2010*, Leonard J. Schulman (Ed.). ACM, 171–180. <http://doi.acm.org/10.1145/1806689.1806714>
- Benny Applebaum, Yuval Ishai, and Eyal Kushilevitz. 2006a. Cryptography in NC0. *SIAM J. Comput.* 36, 4 (2006), 845–888.






Fig. 1. Number of seconds taken by MiniSat to invert Goldreich’s function for different values of  $n$ . We use the degree-five predicate  $P_5(x) = x_1 \oplus x_2 \oplus x_3 \oplus (x_4 \wedge x_5)$  and a random bipartite graph of right-degree five.

- Benny Applebaum, Yuval Ishai, and Eyal Kushilevitz. 2006b. On Pseudorandom Generators with Linear Stretch in NC0. In *APPROX-RANDOM*. 260–271.
- Eli Ben-Sasson and Avi Wigderson. 2001. Short proofs are narrow - resolution made simple. *J. ACM* 48, 2 (2001), 149–169.
- Andrej Bogdanov and Youming Qiao. 2009. On the Security of Goldreich’s One-Way Function. In *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques, 12th International Workshop, APPROX 2009, and 13th International Workshop, RANDOM 2009, Berkeley, CA, USA, August 21-23, 2009. Proceedings (Lecture Notes in Computer Science)*, Irit Dinur, Klaus Jansen, Joseph Naor, and José D. P. Rolim (Eds.), Vol. 5687. Springer, 392–405. <http://dx.doi.org/10.1007/978-3-642-03685-9>
- James Cook, Omid Etesami, Rachel Miller, and Luca Trevisan. 2009. Goldreich’s One-Way Function Candidate and Myopic Backtracking Algorithms. In *Theory of Cryptography, 6th Theory of Cryptography Conference, TCC 2009, San Francisco, CA, USA, March 15-17, 2009. Proceedings (Lecture Notes in Computer Science)*, Omer Reingold (Ed.), Vol. 5444. Springer, 521–538. <http://dx.doi.org/10.1007/978-3-642-00457-5>
- Niklas Eén and Armin Biere. 2005. Effective Preprocessing in SAT Through Variable and Clause Elimination. In *SAT (Lecture Notes in Computer Science)*, Fahiem Bacchus and Toby Walsh (Eds.), Vol. 3569. Springer, 61–75.
- Niklas Eén and Niklas Sörensson. 2003. An Extensible SAT-solver. In *SAT (Lecture Notes in Computer Science)*, Enrico Giunchiglia and Armando Tacchella (Eds.), Vol. 2919. Springer, 502–518.
- Oded Goldreich. 2000. Candidate One-Way Functions Based on Expander Graphs. *Electronic Colloquium on Computational Complexity (ECCC)* 7, 90 (2000). <http://eccc.hpi-web.de/eccc-reports/2000/TR00-090/index.html>
- Dmitry Itsykson. 2010. Lower Bound on Average-Case Complexity of Inversion of Goldreich’s Function by Drunken Backtracking Algorithms. In *CSR (Lecture Notes in Computer Science)*, Farid M. Ablayev and Ernst W. Mayr (Eds.), Vol. 6072. Springer, 204–215.
- Dmitry Itsykson and Dmitry Sokolov. 2011. Lower Bounds for Myopic DPLL Algorithms with a Cut Heuristic. In *Algorithms and Computation - 22nd International Symposium, ISAAC 2011, Yokohama, Japan, December 5-8, 2011. Proceedings (Lecture Notes in Computer Science)*, Takao Asano, Shin-Ichi Nakano, Yoshio Okamoto, and Osamu Watanabe (Eds.), Vol. 7074. Springer, 464–473. <http://dx.doi.org/10.1007/978-3-642-25591-5>
- Dmitri Itsykson and Dmitry Sokolov. 2012. The complexity of inversion of explicit Goldreich’s function by DPLL algorithms. *Zapiski Nauchnykh Seminarov POMI* 399 (2012), 88–108.

- Dmitri Itsykson and Dmitry Sokolov. 2013. The complexity of inversion of explicit Goldreich’s function by DPLL algorithms. *Journal of Mathematical Sciences* 188, 1 (2013), 47–58. <http://link.springer.com/article/10.1007/s10958-012-1105-8>
- Kazuo Iwama and Shuichi Miyazaki. 1999. Tree-Like Resolution Is Superpolynomially Slower Than DAG-Like Resolution for the Pigeonhole Principle. In *Proceedings of ISAAC (Lecture Notes in Computer Science)*, Vol. 1741. 133–142.
- Rachel Miller. 2009. Goldreich’s One-Way Function Candidate and Drunken Backtracking Algorithms. (2009). <http://people.csail.mit.edu/rmiller/ram9a-dmp-thesis.pdf> Distinguished Majors Thesis.
- Saurabh Kumar Panjwani. 2001. An Experimental Evaluation of Goldreich’s One-Way Function. (2001).

#### A. TESTING THE PREDICATE $P$

Each theorem in Section 2 asserts the existence of a test for the suitability of a predicate  $P$  for use by Goldreich’s function. The details of these tests emerge as each theorem is proved. A reader who wishes to understand the statements of the theorems need only refer to properties (A), (B) and (B’) described in Definition 2.3 in order to understand the kinds of predicates that will pass this test.

A reader studying the proofs in this paper might find it useful to see in one place all of the properties we require of the predicate in each theorem. As a convenience, we gather them here. Note that every test described below can be performed in time  $2^{O(d)}$ , as required by property (C).

- For Theorem 2.5, which bounds the expected size of pre-images,  $P$  should have the form  $P_{h,Q} = x_1 \oplus \dots \oplus x_{d-h} \oplus Q(x_{d-h+1}, \dots, x_d)$  or be  $\delta$ -collision averse (Definition 3.7). Here, the value of  $h$  can be any function of  $d$  as long as  $d-h = \Omega(d)$  (property (B) from the theorem statement). The value of  $\delta$  is determined in the proof of Lemma 3.9.
- For Theorem 2.8 (about drunk backtracking algorithms) we additionally require  $P$  to be  $h$ -robust (Definition 4.8). The value of  $h$  may grow as  $cd$  for any constant  $0 \leq c < \frac{1}{2}$  (property (B’) from the theorem statement).
- For Theorem 2.11 (about myopic backtracking algorithms) the predicate must satisfy all the above conditions, and must also be  $(h, \epsilon_{\text{bal}})$ -balanced (Definition 6.1) for some  $\epsilon_{\text{bal}} = 2^{-\Omega(d)}$ .
- Theorem 2.14 concerns DPLL drunk and DPLL myopic algorithms. For DPLL drunk algorithm, the test is the same as for Theorem 2.8. For DPLL myopic algorithms, the predicate must be  $h$ -nonmonotone (Definition 7.3) for  $h = d/2 - \Omega(d)$  and satisfy the test from Theorem 2.11.